

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

96 JAN 25 11:13
010 ALBUQUERQUE N.M.

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

EnRe Corporation

Ampolex (USA), Inc. - AGENT

3. Address and Telephone No.

4940 Broadway #200
San Antonio, TX 78209

1050 17th Street, #2500
Denver, CO 80265

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1,000' FNL & 1,300' FEL
Section 2-T27N-R2W

(303) 595-9000

5. Well Designation and Serial No.

701-94-0010

6. Indian, Allottee or Tribe Name

Great Field Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Leavry Canyon 2A #1

9. API Well No.

30-039-25228

10. Field and Pool, or Exploratory Area

W. Puerto Chiquito Mancos

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Set cement retainer @ 6,800' to abandon open hole section 6,900' - 7,327'.
2. Place 5 sk cement plug on top of bridge plug.
3. Place 100' cement plug inside of 7" casing with \pm 25 sx from 314' - 414' across surface casing seat @ 364'.
4. Place 10 sk cement @ surface, 0 - 45'.
5. Cut off wellhead and install dry hole marker.
6. Rehabilitate wellsite and re-seed.

14. I hereby certify that the foregoing is true and correct

Signed

Robert C. Arceneaux

Title

Robert C. Arceneaux - AGENT
Senior Petroleum Engineer

Date

24/January/1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Chief, Lands and Mineral Resources

Date

FEB 23 1996

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side