STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Name of Reservoir on Pool Type of Page Name of Reservoir on Pool Type of Page New of Art Lift Page P	Decator	Union	oil Co	mpan	y of Californ	ia Lease _	Rincon	Unit		Well No.	171M	
NAME OF RESERVOIR OR FOOL Type of PAOL PROD. P					dba Unoc	a⊥			Cour	nty Rio	Arriba	
Completion Dakota Cas Flow Tubing						TYPE OF P	ROD.	METHOD OF PROD.			PROD. MEDIUM	
PRE-FLOW SHUT-IN PRESSURE DATA Upper Hour, date shut-in 11/25/92 8:55 am		Mesa	Verde			Gas		Flow			Annulus	
	_	Dakot	a			Gas	Gas		Flow		Tubing	
No No No No No No No No					PRE-FLO	W SHUT-IN P		ATA				
Casing 440 No Stabilized? (Yes or No) Casing 440 No Stabilized? (Yes or No) No No No No No No No		Hour, date	shul-in		Length of time shu	l-in	81 press, paig			Stabilized? (Yes or No)		
Source S		11/25	5/92 8	:55 a								
Tubing 1260 No FLOW TEST NO. 1 Stabilized? (Yes or No) Sta	Lower	Hour, date	shul-in		Length of time shu	Length of time shut-in		SI press. psig				
Convenenced at froor, date)			5/92 8	:55 a	m 7 c	7 days		Tubing 1260		No		
Time Lipsed Time Upper Completion Lower Completion Lower Completion TEMP. 12/02/92 24 hours Casing 480 Tubing 1310 79° Q = 766 MCF/D 12/03/92 48 hours Casing 480 Tubing 480 73° Q = 851 MCF/D 12/03/92 48 hours Casing 480 Tubing 480 73° Q = 851 MCF/D Production rate during test Dil: BOPD based on Bbls. in Hours GOR Gas: MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Completion Length of time shut-in Si press, psig Stabilized? (Yes or No) Length of time shut-in Length of time shut-in Si press, psig Stabilized? (Yes or No)						FLOW TEST	NO. 1					
TIME	onimenced	at (hour, de	10)* Dece	ember	1, 1992 9:	15 am	Zone prod	ueing (Upp	er er Lowerk	Lower		
SINCE* Upper Completion Lower Completion TEMP.			Ī			SURE	PROD. Z	ONE		BEMARKS		
12/03/92 48 hours Casing 480 Tubing 480 73° Q = 851 MCF/D Production rate during test Oil:BOPD based onBbls. inHoursGravGOR Boss:MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Mour. date shul-in					Upper Completion	Lower Completion	TEMP.	<u>'. </u>		(Mariting)		
Production rate during test Dil: BOPD based on Bbls. in Hours Grav GOR Base: MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shul-in	12/02/92		24 hours		Casing 480	Tubing 1310	79°		Q = 766 MCF/D			
Production rate during test Dil:BOPD based onBbls. inHoursGravGOR BoysMCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Completion	12/03/92		48 hours		Casing 480	asing 480 Tubing 480		73° Q =		851 MCF/D		
Production rate during test Dil:BOPD based onBbls. inHoursGravGOR BoysMCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Completion												
Dil:BOPD based onBbls. inHoursGravGOR MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shul-in							· ·			•		
Dil:BOPD based onBbls. inHoursGravGOR MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper			-							- · · · · · · · · · · · · · · · · · · ·		
Dil:BOPD based onBbls. inHoursGravGOR MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shul-in			 									
Dil:BOPD based onBbls. inHoursGravGOR MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shul-in	roducti	on rate o	luring test				<u></u>					
MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Completion Length of time shut-in St press. psig Stabilized? (Yes or No) Hour, date shut-in Length of time shut-in St press. psig Stabilized? (Yes or No)			_			DLI. :	_	Llour	(- -	GOR	
Upper Completion Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No) Hour, date shut-in Length of time shut-in SI press, psig Stabilized? (Yes or No)	Oil:			_ BOF	D based on	DOIS. II	·	Hous.		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Upper Completion Length of time shut-in Si press. psig Stabilized? (Yes or No) Hour, date shut-in Length of time shut-in Si press. psig Stabilized? (Yes or No)	325:				MCF	PD; Tested thru	(Orifice of	r Meter):			
Upper Completion Length of time shut-in St press. psig Stabilized? (Yes or No)					MID-TI	ST SHUT-IN P	RESSURE I	ATAC				
Hour, date shut-in Length of time shut-in \$1 press, pelg Stabilized? (Yes or No)		1	shul-in		Length of time shu	ngth of time shut-in		Si press. psig			Stabilized? (Yes or No)	
Completion	Lower	Hour, date	shul-in		Length of time sho	it-in	SI press. peig			Stabilized? ((es or No)	

DEC2 2 1992

(Continue on reverse side)

OIL CON. DIV.

FLOW TEST NO. 2

mmenced at (hour, d	a(e) * *		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE			
(hour, date)	\$INCE **	Upper Completion	Lower Completion	TEMP.	new.	ARK8	
							
,							
	- 						
	<u> </u>				(
duction rate o							
:	ВОР	D based on	Bbls. in	Hours.	Grav	GOR	
s:		MCF	PD: Tested thru	(Orifice or Meter)):	-	
narks:							
					_		
•				mplete to the best	t of my knowledge.		
proved	EC 🐉 🕹 1 9 9	2	_ 19 O	perator Union	Oil Company of	California dba	
New Mexico C	il Conservation D	Division		•			
			В	ySandy	Liese San	dycor	
Original S	igned by CHARLE	S GHOLSON			1 01 1	1	
	3	3 0.102.301-	T	ide <u>Gener</u>	al Clerk		
	nl a gas inspec				7/92		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not temain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, as hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in striplicate within 13 days after completion of the test. Tests shall be filed with the Astec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).