

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SF 079298

6. If Indian, Allottee or Tribe Name

N/A

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Union Oil Company of California

3. Address and Telephone No.

P.O. Box 2620, Casper, WY 82602, 307-234-1563

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 14, T27N, -R7W
790' FNL & 445' FWL

RINCON UNIT

8. Well Name and No.

RINCON UNIT #133E

9. API Well No.

30-039-25187

10. Field and Pool, or Exploratory Area

BAS DAK/BLANCO MV

11. County or Parish, State

RIO ARriba CO., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/12/94 THRU 7/18/94

DRLG AHEAD W/NO PROBLEMS, 5,192'. SLUG PIPE, DROP SURVEY. TRIP FOR BIT. TIH W/BIT. TAGGED @ 375'. ATTEMPT TO WORK FAST W/O SUCCESS TOOH. L/D BIT TIH W/6" O.D. BIT SUB. ATTEMPT TO WORK THRU 375' W/O SUCCESS. POOH. R/U WIRELINE RUN CCL (2" O.D.) TAG @ 375'. APPEARS GUIDE SHOE BACKED OFF. TIH W/7-1/8" O.D. CONCAVE MILL - 2 JUNK SUBS ON 6" DC'S TO 375' MILL & REAM FROM 375'-422'. W/PUMP OFF THE HOLE & NO ROTATION WORK FROM 422'-370' W/NO PROBLEMS. TIH W/REAMING DC'S & DP APPEARS TO BE CHASING DEBRIS ON BTM. MILL & REAM @ 5,192'. TOH W/MILL. TIH W/BIT & TAG OBSTRUCTION @ 564'. TOH W/BIT. TIH W/MILL. MILL ON JUNK 564' FOR 12 MIN. & PUSH JUNK TO BTM 5,194' & MILL TO 5,198'. TOH W/MILL. TIH W/BIT TO 5,198' DRLD TO 5,715'.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Drilling Secretary

October 21, 1994

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

OCT 31 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

BY

FARMINGTON DISTRICT OFFICE

RINCON UNIT #133#
PAGE TWO

7/12/94 THRU 7/18/94

LOST COMPLETE RETURNS. PUMPED 400 BBL PREMIX, 40% M.F. W/3 #/BBL CALCAR. PUMPED 300 BBL MUD MIXED @ 9.1 PPG. PU 10 STDS TO 4,828' W/40-60K OVER STRING WT. PUMP PREMIX, 45% MF W/3 #/BBL CALCAR. REGAINED RETURNS AFTER PUMPING 80 BBL. TIH TO 5,540'. TAGGED BRIDGE & PUMPED 620 BBL OF LCM MATERIAL, 45% MAGNA FIBER 3#/BBL CALCAR. PU TO 5,260'. MIX & PUMP 300 BBL LCM DOWN BACKSIDE, 45% MF W/6 #/BBL CEDAR FIBER, 3#/BBL CALCAR & 400 BBL SAME LCM DOWN DP. WAITED 1.5 HRS. PUMPED 200 BBL LCM, 45% MF, 3 #/BBL CALCAR DOWN DP W/300 PSI. REGAINED RETURNS. MIXED & PUMPED LCM DOWN DP W/600 PSI WHILE MOVING PIPE. TIH TO 5,540'. HAD FULL RETURNS W/600 PSI. TIH TO 5,665'. FLUID LEVEL 30' BELOW ROTARY. CIRCULATE @ 600 PSI W/75% RETURNS. DRLD TO 5,945' W/LOSSES OF 25% USING 12% LCM. LOST COMPLETE RETURNS @ 5,945'. SPOTTED 400 BBL LCM FROM PREMIX TANK W/45% MAGNA FIBER W/3 #/BBL CALCAR. TOH 10 STD TO 5,010'. MIX 400 BBL LCM. TIH TO 5,945' SPOTTED 400 BBL FROM PREMIX TANK W/48% MAGNA FIBER W/4 #/BBL CALCAR. TOH TO 5,440' & MIX 400 BBL LCM.

SURVEYS: 1/2° @ 4,735', 3/4° @ 5,192'