Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR RUPEAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. Contract 701-90-0001 **SUNDRY NOTICES AND REPORTS ON WELLS** Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals Jicarilla Apache 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well N/A 8. Well Name and No. Oil Well Gas Well Name of Operator Jicarilla 28B-American Hunter Exploration, Ltd.
3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., K., M., of Survey Description) W. Puerto Chiquito 11. County or Parish, State 455'FNL 1510'FEL Sec. 28 T27N R2W Rio Arriba, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Abandon nen: Change of Plans Recompletion New Construction Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice CON. DIV Altering Casing Conversion to Injection 」Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinen; dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* ember 2, 1992 Drilled to 7,126', tripped for logs, ran DILL, GR-CNL-CDL, SONIC logs 7126' to surface casing November 2, 1992 Depth 7,157', ran 173 Jts. 7-5/8" O.D. 26.41b J&N Grade 8RT LT&C casing set at 7,157'; Cemented with: 1st stage, 355 SX 50/50 POZ "B", 2% GEL, 61b SX Salt, 61b SX. GIL plus 50 SX. Class "G", 0.75% HALAD 322, P.D. 3:30AM 11-3-92, preceded by 20 BBL. Mud flush, displaced with fresh water, 2nd stage (multistage cementer at 3,997'), 375 SX. 65/35 POZ "B", 12% (multistage cementer at 3,997'), 375 SX. 65/35 POZ "B", 12% of GEL, 41b SX. GIL plus 110 SX. 50/50 POZ, 2% gel, 61b SX, saPt, 61b SX GIL plus 25 SX. Class "B", 0.75% HALAD 322, P.D. 9:00 AM 11-3-92, displaced with water, good circulation throughout job. 14. I hereby certify that the foregoing is true and correct PROD. SAP (This space for Federal or State office 

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.