STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	·	CONOCO	IIIC	lesse S	Well Lesse SAN JUAN 28-7 UNIT No. 181M (MD)					
Location of Well:	Unit _D	Sec. <u>03_</u> '	Г w p27	Rge)7	County _	RIO ARRIBA		
	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Oil or Ges)		METHOD OF PROD. (Flow or Art. Lift)		PROD, MEDIUM (Tbg. or Cog.)		
Upper Completion				GAS		FLOW		TBG.	_	
Completion DAKOTA			GAS		FLOW		TBG.			
			PRE-FLO	W SHUT-IN P	RESSURE I	DATA				
Upper Completion 10-08-97		3-D2	Length of time shut-in 3_DAYS		Si press. psig		Stabilized? (Yes or No) HO Stabilized? (Yes or No)			
Lower Completion			·	Length of time shut-in		0		NO		
		<u> </u>		FLOW TEST	NO. 1	·				
Conmenced	at thour, dat	he)* 10_1	1_97		Zone preducing (Upper or Lower):			UPPER		
TIME (hour, date)		LAPSED TIME SINCE#	PRES: Upper Completion	Lower Completion	PROD. 20 TEMP		REMARKS		_	
10-0	9-97	1-DAY	233			BO	CH ZONE	S SHUT-IN		
10-10-97		2-DAYS	241	0		ВО	BOTH ZONES SHUT-IN		_	
10-1	1-97	3-DAYS	243	0		BO	rh zone	S SHUT-IN	_	
10-12-97		1-DAY	222	0	<u> </u>	UPPER ZON		E FLOWING	 .	
10-1	3-97	2-DAYS	219	0		UP	PER ZON	F FLOWING	-	
		uring test	DAKO	_				COR	 -l	
Oil:		BOP	D based on	Bois. n	<u> </u>	Hours.	Grav			
G25:			-	PD; Tested thru						
, 				ST SHUT-IN P	RESSURE I	DATA	Stabilit	ed? (Yes or No)		
Upper Completion			Langth or time six	Length of time shut-in						
Lower Completion			Length of time she	Length of time shut-in		Stabilized? (Yes or No)				
<u> </u>			• •			N DEC 1 0 1997				
				(Continue on	reverse side	, 011	CON.			

THE STATE CONTRIBUTION OF THE STATE OF THE S

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Operator

Title Field

Date 12-2-97

By _

hereby certify that the information herein contained is true and complete to the best of my knowledge.

_____ 19 ____

A packer leakage test shall be commenced on each multiply completed well within en davs after actual completion of the well, and annually thereafter as prescribed by the er authorizing the multiple completion. Such tests shall also be commenced on all triple completions within seven days following recompletion and/or chemical or fractreament, and whenever remedial work has been done on a well during which the ker or the tubing have been disturbed. Tests shall also be taken at any time that commission is suspected or when requested by the Division.

Johnny Rolunas

Deputy Oil & Gas Inspector

oproved <u>DEC 4 5 1997</u>
New Mexico Oil Conservation Division

At least 72 hours prior to the commencement of any packer leakage test, the operator il notify the Division in writing of the exact time the test is to be commenced. Offset rators shall also be so notified.

The packer leakage test shall commence when both zones of the dual completion are t-in for pressure stabilization. Both zones shall remain shut-in until the well-head sture in each has stabilized, provided however, that they need not remain shut-in more n seven days.

For Flow Test No. 1, one zone of the dual completion shall be produced at the normal of production while the other zone remains shut-in. Such test shall be continued for in days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on mitial packer leakage test, a gas well in being flowed to the atmosphere due to the lack i pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be shut-in, in accorte with Paragraph 3 above.

Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow t No. 1. Procedure for Flow Test No. 2 is to be the same to for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

CONOCO INC

Grod.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil sone tesus all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas deal completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Asset District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leskage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas somes only) and gravity and GOR (oil zones only).