

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENRE CORPORATION

3. Address and Telephone No.

210 8260601

P. O. BOX 6027
SAN ANTONIO, TEXAS 78209

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1015' FNL & 790' FEL

Sec 18 T27N, R2W N.M.P.M.

5. Lease Designation and Serial No.

701-94-0010

6. If Indian, Allottee or Tribe Name

Yavapai Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

LEAWY CANYON 18A #1

9. API Well No.

10. Field and Pool, or Exploratory Area

GAUAN PICTURED CLIFFS

11. County or Parish, State

RIO ARriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log (form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11/30/94 Spud 5:45pm. Drill 12 1/4" hole to 278'. Ran 7jts 9 5/8", 36#, K-SS, Rg-III csg to 272' KB. Halliburton cement w/ 150 sx Class 'B' cmt w/ 2% CaCl, 3% NaCl, 1/4#/sx colloids. Plug down 3:30am 12/1/94.

12/6/94 TD @ 3920' 7 7/8" hole. Ran DILL, MICRO, CD/GR logs, Numar MRIL. Ran 91jts 4 1/2", 11.6#, N-80, ST&C csg to 3920'. Cement 1st stage w/ 275 sx Class 'B' cmt w/ 2% gel, 1/4#/sx floccul, 50-50 poz. Cement 2nd stage w/ 590 sx Halliburton Lts. Circ. 23 Bbl cmt to surface. Rig Released 2am 12/7/94.

14. I hereby certify that the foregoing is true and correct

Signed

Title VP

Date

12/10/94

(This space for Federal or State office use)

Approved by

Title

for Chief, Lands and Mineral Resources

Date

DEC 19 1994

Conditions of approval, if any: