

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

701-94-0011

6. If Indian, Allottee or Tribe Name

Micaculla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Los Indios Canyon II #1

9. API Well No.

10. Field and Pool, or Exploratory Area

W. Paces Chiquito Marcos

11. County or Parish, State

Rio Arriba NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

ENRE CORPORATION

3. Address and Telephone No.

P. O. BOX 6027
SAN ANTONIO, TEXAS 78209

210 8260681

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2400' FSL & 2100' FEL
Sec 11 T27N, R1W

LC; LOS
INDIOS
ENTRA.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion or well completion or recompletion report and log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9 DEC '94 - SPUD @ 04:30 hrs

10 DEC '94 - DRILL 12.25" hole to 400'. Ran 10 jts 9.625" 36# K-SS STFC CSG to 391' KB.
CEMENTED CSG w/ 225 SX class 'B' w/ 2% CaCl, 3% NaCl, 0.25 #/sx flocc.

31 DEC '94 - DRILL 8.75" hole to 5416'. Ran DILL, SDL/DSN, LSS logs.

4 JAN '95 - DRILL 8.75" hole to 5726'. Ran 154 jts 7.00" 23# K-SS FN-BO LTFC & STFC
Rg II & Rg III CSG to 5699' KB w/ DV tool @ 5015' KB. CEMENT 1ST STAGE
w/ 150 SX 50/50 POZ class 'B' w/ 2% gel, 0.25 #/sx flocc, 0.4% HALAD 344. CEMENT
2ND STAGE w/ 770 SX class 'B' foamed w/ N₂. Tailed w/ 110 SX 50/50 POZ. Topped
out w/ 100 SX class 'B'.

14 JAN '95 - DRILL 6.25" hole to 6511' MD. BHL @ 6429' MD - 29.10°, S 75.40° E, 6325' TVD,
117' N, 841' E

(CONTINUED ON NEXT PAGE)

14. I hereby certify that the foregoing is true and correct

Signed

Title

JP

Date

5 MAY 95

(This space for Federal or State office use)

Approved by

Title

for Chief, Lands and Mineral Resources

Date

JUL 18 1995

Conditions of approval, if any: