

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

701-94-0011

6. If Indian, Allottee or Tribe Name

Jicarilla Apache
N.M.

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

ENRE CORPORATION

3. Address and Telephone No.

P. O. BOX 6027
SAN ANTONIO, TEXAS 78209

210 8260681

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1395' FSL & 2180' FEL
SEC 15 T27N, R1W

WC; LOS
INDIOS
ENTRA.

8. Well Name and No.

Los Indios Canyon 15J #1

9. API Well No.

10. Field and Pool, or Exploratory Area

W. PUEB. CMT. MARCOS

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

20 DEC '94 - SPUD @ 13:00 hrs.

21 DEC '94 - RAN 10 JTS 10.75" 40.5# K-55 8rd STEC Rg III csg to 383' KB. Cemented w/ 275 SX CLASS B w/ 28 CaCl, 3% NaCl, 0.25 #/sx cello-seal. Plug down @ 15:30 hrs. Circ 22 SX CNT to surface

13 JAN '95 - Drill 9.875" hole to 6719' KB, Run DILL, CDHGR, Sonic logs

15 JAN '95 - RAN 156 JTS 7.625" 26.4# N-80 Rg III w/ DV Tool @ 5689' to 6718' KB. CEMENTED 1st STAGE w/ 110 SX HOWCO LTE & 125 SX 50/50 Poz. CEMENTED 2nd STAGE w/ 760 SX standard cement foamer w/ N₂, tailed w/ 220 SX 50/50 Pozmix & 100 SX down annulus for top off.

(CONTINUED ON ATTACHED PAGE)

14. I hereby certify that the foregoing is true and correct

Signed

Title

VP

Date

5 MAY 1995

(This space for Federal or State office use)

for Chief, Lands and Mineral Resources

Approved by

Title

Date

JUL 18 1995

Conditions of approval, if any: