STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page Revised 10/01/7

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operate	or _	UNIO	N OI	L CON	1PAN'	<u> </u>	CALIF	ORNIA	_ Lease _	RINCO	N UNIT		No	
Location of Well	n : Uni	<u> F</u>	Se	c. <u>32</u>	Tv	ا vp.	DBA UNO	OCAL 7N	Rge	6W		Cou	nty	RIO ARRIBA
NAME OF RESERVOIR OR POOL							TYPE OF	FF.00.	OD. METHOD OF PRO).	PROD, MEDIUM (Tbg. or Cag.)		
Upper Completio	Upper BLANCO MESA VE				ERDE			GAS		FLOW			TUBING	
Lower Compiello							GAS			FLOW			TUBING	
							PRE-FI	LOW S	HUT-IN I	PRESSURE	DATA			
Upper Completio	empletion APRIL 28, 1996 10:30AM					3 DA	3 DAYS		TBG. 400			Stabilized? (Yes or No) NO		
Lower Completio	Lower 1 I					Length of time shul-in 30AM 3 DAYS			TBG. 800			Stabilized? (Yes or No) NO		
			. м	ΔV 01	10	106	10.507		W TEST				LOWER	
·			MAY 01, 19			PRESSURE			··	Zone producing (Up) PROD. ZONE				
(hour, date)			SINCE*			Upper Completion		Lawer Completion		TEMP.		REMARKS		
05/02/96			24 HRS.		ᆚᆚ			TRG	140	59°		Q = 511 MCF/D		MCF/D
05/03/96			7			SG. 425 BG. 425 TBG. 110			62° 0		<u> </u>	= 469 MCF/D		
			···	. <u></u>	- -	·		 		ļ. <u></u>				
·					- -			ļ						
					- -							•		
roducti	on rai	e du	ing te	st t			-	<u> </u>	•	<u></u>	J			·
Production rate during test Dil: BOPD based on							_ Bbls. in		Hours	G	rav	GOR		
;as:							MCF	PD; Te	sted thru	(Orifice or	Meter):	·		-
					يوبيء سند بنسا		MID-TI	est sh	UT-IN PE	ESSURE D	ATA			•
Upper ompletion					gth of time shut-in			II press. psig			Stabilized? (Yes or No)			
Lower completion	1				Length of time shut-in			SI press. paig			Stabilized? (Yes Or No)		
									•					

PEGASAA Maria

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, d	late) = =		Zone producing (Upper or Lowerk				
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE			
(hour date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS		
	İ)			
·							
	-						
							
Production rate of	luring test						
Oil:	BOPI	D based on	Bhle in	Hours	Grav GOR		
					al.		
Gas:		MCFF	D: Tested thru	(Orifice or Meter)			
Kemaiks.							
	·						
hereby certify the	hat the information	on herein containe	d is true and con	nplete to the best	of my knowledge.		
Approved	Johnny Role	24. C	19 O	perator UNIO.N	OIL COMPANY OF CALIFORNIA DBA		
New Mexico O	il Conservation D	ivision		,	UNOCAL		
	MAY 1 7		Ву		Corre		
Зу			T est.		ction Foreman		
10	EPUTY OIL & GAS	As as as as		uç			
Tide		·	Da	May 14	1, 1996		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such term shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Notes if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in it produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).