

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-039-25483

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
UNION OIL COMPANY OF CALIFORNIA

3. Address of Operator  
P.O. Box 2620, Casper, WY 82602 (307) 234-1563 Ext. 116

4. Well Location  
Unit Letter F : 1815 Feet From The North Line and 1840 Feet From The West Line  
Section 32 Township 27N Range 6W NMPM Rio Arriba County

7. Lease Name or Unit Agreement Name

RINCON UNIT

8. Well No.  
166E

9. Pool name or Wildcat  
Basin/Dak/Blanco M.V./So. Blanco P.O.

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: OIL CON. DIV. ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: SPUD REPORT ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU Aztec Well Service Rig #222. Spud 12 $\frac{1}{4}$ " hole @ 4:30 a.m. 9-8--95. Drilled to 375'. Drop survey and POOH. Ran and cemented 8 jts. (354') 9-5/8", 36# K-55, ST&C 8rd new casing landed @ 370'. Cemented w/225 sx Class "G" cement w/2% CaCl<sub>2</sub>, 1/4#/sx D-29 (mixed @ 15.8 ppg, yield 2.28 cu.ft./sx) circulated 35 sx cement to surface. Bumped plug. WOC 3 hrs. NU BOP. Tested 9-5/8" csg, blind rams, pipe rams, manifold and floor valves to 250# low and 2000# high. Drilled cement and guide shoe. Drilled to 2308'. Drilling Inc.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jim Benson TITLE Drilling Superintendent DATE 9-12-95  
TYPE OR PRINT NAME Jim Benson TELEPHONE NO. (307) 234-1563 Ext. 11

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE SEP 14 1995  
CONDITIONS OF APPROVAL, IF ANY: