STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISIO

API#

30-039-25591

Page 1 Revised 1C01/58

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well 100M BURLINGTON RESOURCES OIL & GAS CO. SAN JUAN 27-5 UNIT No. Operator Location 027N 005W **RIO ARRIBA** of Well: ı 01 Rge. County Unit Twp. Sect PROD. MEDIUM TYPE OF PROD. METHOD OF PROD. NAME OF RESERVOIR OR POOL (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper MESAVERDE Gas Flow Tubing Completion Lower Gas Flow Tubing DAKOTA Completion PRE-FLOW SHUT-IN PRESSURE DATA Stabilized? (Yes or No) Length of time shut-in SI press. psig Upper Hour, date shut-in Completion 05/09/2001 120 Hours 354 Lower Completion 05/09/2001 72 Hours 362 FLOW TEST NO. 1 **LOWER** Commenced at (hour.date)* 05/12/2001 Zone producing (Upper or Lower) PROD. ZONE TIME LAPSED TIME **PRESSURE** TEMP REMARKS SINCE* Upper Completion Lower Completion (hour.date) 05/13/2001 362 172 96 Hours 190 120 Hours 380 05/14/2001 Production rate during test GOR Grav. Oil BOPD based on Bbls. in Hours. MCFPD: Tested thru (Orifice or Meter): Gas MID-TEST SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Upper Completion Length of time shut-in Stabilized? (Yes or No) Hour, date shut-in SI press. psig Lower Completion 320 3666401

(Continue on reverse side)

FLOW TEST NO. 2

mmenced at (hour, da	ate)**			Zone producing (Upper or Lo	wer):
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS
		Upper Completion	Lower Completion	TEMP.	
			-		
orli:BOPD based on					
ias:		MCFP	D: Tested thru (C	rifice or Meter):	
Damarke:					
Cemarks.					
				, the bast of my knowledg	e.
hereby certify the	at the information n	lerem contained is tru	e and complete to	the best of my knowledg	
Approved	0014 1 4	2001	19	Operator Burlingt	on Resources
	Dil Conservation Di			ΩL	Prince 1
		HARAT. PANN		By	U.47:
					
•	ALC: MICHAEL WITH			Title Onerations A	ssociate
Ву	Y OIL & GAS INSI			Title Operations A	ssociate

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which, he packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the web-head pressure in each has stabilized, provided however, that they need not remain skut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a derdweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at tifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired or may be requested on wells which have previously shown questionable test dita.
- may be requested on wells which have previously shown questionable less data 24-hour oil zone tests all pressures, throughout the entire test shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Offi Conservation Division or, Northwest New Mexico Packer Leakage Test Form Revised 10-(1-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)