
Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



	ne de la companya de	SF-078972	
	SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
	Do not use this form for proposals to drill or to deepen or reentry to a different resemble.	1:01	
	Use "APPLICATION FOR PERMIT-" for such proposals		
	SUBMIT IN TRIPLICATE 070 2	7., IRUNIT OR CA, AGREEMENT DESIGNATION	
1.	TYPE OF WELL	8. WELL NAME AND NO.	
	OIL WELL GAS WELL OTHER :	SAN JUAN 28-7 #182M	
2.	NAME OF OPERATOR	9. API WELL NO.	
	CONOCO INC.	30-039-25689	
3.	ADDRESS AND TELEPHONE NO.	10. FIELD AND POOL, OR EXPLORATORY AREA	
	10 DEST DRIVE, STE. 100W MIDLAND, TX 79705 915-686-5424	BLANCO MV / Desir DE	
4.	LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)	11. COUNTY OR PARISH, STATE	
	1610' FSL-1674' FEL, SEC: 03, Ť-27-Ñ, R-7-W UNIT "J"	RIO ARRIBA, NM	
12.	2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	TYPE OF SUBMISSION TYPE OF ACTION		
	Notice of IntentD) = (2) Abandonment	Change of Plans	
ŀ		New Construction	
	Subsequent Repart SEP 2 5 1897 Recompletion Plugging Back	Non-Routine Fracturing	
	Final Abandonment Notice Casing Repair	Water Shut-Off	
	0 L ((6)) Altering Casing	Conversion to Injection	
	Other: spud, cement, & casing re	port Dispose Water	
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)	
13.	 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 		
	8/30/97 Spudded well.	to ans work.)	
	8/30/97 Drilled surface hole. Ran 5 joints 9-5/8", 36#, 8rd Lt & C, K-55 casing. Landed at 281	Cement with 280 sks. Class B cement with	
	3% CaCl2 and 1/4#/sk Cello Flake. Displaced 18.5 bbls. H20, muddy returns. Bumpe Good returns circ 11 bbls cement.	ed plug at 22:00 a.m. on 8/30/97 with 400 PSI.	
	9/4/97 Ran 81 joints 7", 23# K-55, st & C, 8rd, casing, landed @ 3658'. Cement with 520 sk: CaCl2, 25#/sk Cello Flake., 6.25#/sk Gilsonite. 115 sx Class B cmt w/ 2 % CaCl2 1/4 water., muddy returns. Cement returns 38 bbls approx. 86 sks. Bumped plug at 03:0 returns, thru out job.	sk cello Flake. Displaced with 143.4 bbls of	
	9/4/97 03:00 - 06:00 ND, BOP set slips 67-K cut off NU, WH, pt head 2000 PSI. Held okay.		
	9/10/97 Ran 31 Joint 4-1/2*, 11.6# K-55 casing, 8rd Lt & c; 143 joint 4-1/2*, 10.5# K-55 casing, 8rd ST&C, landed @ 7622'. Cement with 535 sx - 50/50 POZ Class b with 4% gel, 2% KCl, .300% FL-32, .300% CD-32, 6.25#/sk Gilsonite, ½#/sk Cello Flake. Followed by 105 sx of Class H with .7508% FL-62 .250% SM, .200% CD-32. Displaced with 120 bbls of H2O, partial returns, floats held. Bumped plug at 08:00 a.m. 9/10/97 with 3000 PSI, final lift pressure was 2500 PSI		
	09/11/97 ND, BOP, set slips w/ R - cutoff; release rig.		
14	14. I hereby certify that the foregoing is true and correct DEBRA BEMENDERFER		
L	SIGNED ALLE AGENT FOR CONOCO IN	C. DATE 9/22/97	
	(This space for Federal or State office use)		
	APPROVED BY TITLE	DATE	
	Conditions of approval, if any:	CCEPTED FOR RECORD	
Tit	Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		

* See Instruction on Reverse Side **NMOCD**

FARMINGTON DISTRICT OFFICE
BY