Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

Budget Burean No.)1004-0135 Exhibes: Merch 31, \$93
5. LEASE DESIGNATION AND SERIAL NO.

BUREAU OF LAND MANAGEMENT	5. LEASE DESIGNATION AND GETTE THE
	SF 078496A
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
o not use this form for proposals to drill or to deepen or reentry to a different reservoig:	,
o not use this form for proposals to drill of to deeper of rooms, to a such proposals	ľ
Use "APPLICATION FOR PERMIT-" for such proposals	7. IF UNIT OR CA, AGREEMENT DESIGNATION
SUBMIT IN TRIPLICATE	SAN JUAN 28-7
	8. WELL NAME AND NO.
TYPE OF WELL	#214M
OIL WELL GAS WELL OTHER :	
NAME OF OPERATOR	9. API WELL NO.
CONOCO INC.	30-039-25793
ADDRESS AND TELEPHONE NO.	10. FIELD AND POOL, OR EXPLORATORY AREA
10 Desta Drive, Suite. 100W Midland, Texas 79705-4500 (915) 686-5424	BASIN DAKOTA
LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)	11. COUNTY OR PARISH, STATE
970' ESL # 270' FEL LINIT I FTTER 'P'. SEC. 04, T27N, R07W	RIO ARRIBA, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
73/05	OF ACTION
TYPE OF SUBMISSION	- Action
Abandonment	Change of Plans
Notice of Intent Recompletion	New Construction
Subsequent Report	Non-Routine Fracturing
Plugging Back	Water Shut-Off
Final Abandonment Notice Casing Repair	
Altering Casing	Conversion to Injection
Other: Spud & csg report - 4	4-1/2" Dispose Water
	(Note: Report results of multiple completion on Well Complet Recompletion Report and Log Form.)
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including earlies directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per	stimated date of starting any proposed work. If well
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Denth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and	stimated date of starting any proposed work. If well trinent to this work.) collar and shoe). Total footage of 7767.71'.
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke.	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Denth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and	stimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" cassing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Celiofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" cassing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
4/21/98 Ran 182 (varied length) jnts of 4-1/2" cassing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	stimated date of starting any proposed work. If well rtinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 77/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	stimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sixs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sixs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	collar and shoe). Total footage of 7767.71'.
Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi.	stimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
A/21/98 Ran 182 (varied length) jints of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi. Thereby certify that the foregoing is true and correct	collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
A/21/98 Ran 182 (varied length) jints of 4-1/2" cassing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead skurry of 430 sixs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sixs Class H land 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# pei. I hereby certify that the foregoing is true and correct SIGNED AUGUSTAN TITLE DEBRA BEMENDERFE	collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
A/21/98 Ran 182 (varied length) jints of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float or Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi. Thereby certify that the foregoing is true and correct	collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-
A/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sixs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sixs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# pei. I hereby certify that the foregoing is true and correct SIGNED WAY - 4 1800 TITLE DEBRA BEMENDERFE	estimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD- S Celloflake. Displaced with 125.5 BBLs of
A/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGlisonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H iand 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi. I hereby certify that the foregoing is true and correct SIGNED TITLE DEBRA BEMENDERFE (This space for Federal or State office use)	collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-2'S Celloflake. Displaced with 125.5 BBLs of CR. As Agent for Conoco Inc. DATE 04/29/98
A/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead sturry of 430 size Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail sturry consisted of 100 size Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi. I hereby certify that the foregoing is true and correct SIGNED Authority that the foregoing is true and correct TITLE DEBRA BEMENDERFE (This space for Federal or State office use)	collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-2'S Celloflake. Displaced with 125.5 BBLs of CR. As Agent for Conoco Inc. DATE 04/29/98
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 size Class B Poz and 32 and 6.25 PPSGlisonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 size Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# psi. I hereby certify that the foregoing is true and correct SIGNED TITLE DEBRA BEMENDERFE (This space for Federal or State office use)	estimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD- S Celloflake. Displaced with 125.5 BBLs of
4/21/98 Ran 182 (varied length) jints of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead slurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# pei. I hereby certify that the foregoing is true and correct SIGNED AND AND AND AND AND AND AND AND AND AN	estimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD- S Celloflake. Displaced with 125.5 BBLs of CR. As Agent for Conoco Inc. DATE 04/29/98 DATE ACCEPTED FOR RECORD
4/21/98 Ran 182 (varied length) jints of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead skurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 sxs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# pei. I hereby certify that the foregoing is true and correct SIGNED	estimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD- S Celloflake. Displaced with 125.5 BBLs of CR. As Agent for Conoco Inc. DATE 04/29/98 DATE ACCEPTED FOR RECORD
4/21/98 Ran 182 (varied length) jnts of 4-1/2" casing , 9.5#/10.5#, J-55, 8rd ST&C (plus float of Depth of collar 7816.77, depth of shoe 7/77. Lead skurry of 430 sxs Class B Poz and 32 and 6.25 PPSGilsonite and 0.25PPS Cellofalke. Tail slurry consisted of 100 axs Class H and 0.07% BA-5L, 0.3% CD-32, and 0.25 PP freshwater, floats held, bumped plug at 9:30 pm on 4-21-98 with 2100# pei. I hereby certify that the foregoing is true and correct SIGNED	estimated date of starting any proposed work. If well rinent to this work.) collar and shoe). Total footage of 7767.71'. d 50/50 4% gel and 0.3% FL-52, 0.3% CD-25 Celloflake. Displaced with 125.5 BBLs of CR. As Agent for Conoco Inc. DATE 04/29/98 DATE ACCEPTED FOR RECORD