Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. LEASE DESIGNATION AND SERIAL NO.

		SF-078570(???)
SUNDRY NOTIC	ES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	to drill or to deepen or reentry to a different reserve	pir.
Use "APPLICATION	N FOR PERMIT-" for such proposals	
SUBMIT IN TRIPLICATE  TYPE OF WELL		7. IF UNIT OR CA, AGREEMENT DESIGNATION SAN JUAN 28-7
		8. WELL NAME AND NO.
OIL WELL 🔲 GAS WELL 🔀	OTHER :	#215M
NAME OF OPERATOR		9. API WELL NO.
CONOCO INC.  ADDRESS AND TELEPHONE NO.		30-039-25801 10. FIELD AND POOL, OR EXPLORATORY AREA
ADDRESS AND TELEPHONE NO.  10 Desta Drive, Suite. 100W Midland, Texas 79705-4500 (915) 686-5424		
LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)		11. COUNTY OR PARISH, STATE
	EC, 04, T27N-R7W, UNIT C (NSL#395	(51) RIO ARRIBA COUNTY, NM
	ATE BOX(s) TO INDICATE NATURE OF NOT	
TYPE OF SUBMISSION		TYPE OF ACTION
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion	New Construction
	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Water Shut-Off
	Altering Casing	Conversion to Injection
	Other: Spud & casing re	
. Describe Proposed or Completed Operations	is (Clearly state all pertinent details, and give pertinent dates, inclu	(Note: Report results of multiple completion on Well Completi Recompletion Report and Log Form.)
	ions and measured and true vertical depths for all markers and zo	·
04/23/98 Spudded well.		
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2.	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r d plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2.	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2.	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2.	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2.	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8" collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r d plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8" collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r d plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8" collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS ( Displaced with 18.62 bbl of fresh water, full r d plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8" collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage arry 200 sxs of Class B, 3% CacL2, .25#PPS (Displaced with 18.62 bbl of fresh water, full rd plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs,
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS (Displaced with 18.62 bbl of fresh water, full rd plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of eturns, cement returns 4 bbl, 18.5 sxs, cement is staying in place.
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8" collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS (Displaced with 18.62 bbl of fresh water, full rd plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of eturns, cement returns 4 bbl, 18.5 sxs, cement is staying in place.
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped  I hereby certify that the foregoing is true and SIGNED	casing, 36#, J-55, 8RD ST&C. Total footage urry 200 sxs of Class B, 3% CacL2, .25#PPS (Displaced with 18.62 bbl of fresh water, full rd plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of eturns, cement returns 4 bbl, 18.5 sxs, cement is staying in place.
04/23/98 Spudded well.  04/23/98 Ran 7 jts. On 9-5/8* collar 236'. Lead slu Class B, .3% Cacl2. floats held. Bumped	casing, 36#, J-55, 8RD ST&C. Total footage arry 200 sxs of Class B, 3% CacL2, .25#PPS (Displaced with 18.62 bbl of fresh water, full rid plug @ 12:50 a.m. on 04/24/98 with 200 psi,	263.27", depth of shoe 279', depth of Cello Flake. Followed by 100 sxs of etums, cement returns 4 bbl, 18.5 sxs, cement is staying in place.  REFER As Agent for Conoco Inc. DATE 04/29/98  ACCEPTED FOR RECORD