UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
LEASE DESIGNATION AND SERIAL NO.

			O. LEASE DESIGNATION AND SERVE NO.
		The second secon	SF 078972
SUNDRY NOTICES AND REPORTS ON WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
Do not use this form for proposal	ls to drill or to deep	pen or reentry to a different reservoir.	
Use "APPLICAT	ION FOR PERMIT	-" for suph preposals	
			7. IF UNIT OR CA, AGREEMENT DESIGNATION
S	SUBMIT IN TRIPLI	CATE IN GO GO GO	
. TYPE OF WELL		UN 8 1998	8. WELL NAME AND NO.
OIL WELL GAS WELL	OTHER [T: 0 1,535 ™	SAN JUAN 28-7 UNIT
. NAME OF OPERATOR		OIL COM DIVI	9. API WELL NO.
CONOCO INC.		OIL GOLGG ENLINO	#156 M
. ADDRESS AND TELEPHONE NO.		BIBIS 8	10. FIELD AND POOL, OR EXPLORATORY AREA
10 Desta Drive, Suite. 100W	Midland, Texas	79705-4500 (915) 686-5424	BLANCO MV/BASIN DAKOTA
LOCATION OF WELL (Footage, Sec., T.,			11. COUNTY OR PARISH, STATE
		R 'O', SEC. 10, T27N, R07W	RIO ARRIBA COUNTY, NM
		O INDICATE NATURE OF NOTICE	
		O INDICATE NATURE OF NOTICE	, REPORT, OR OTHER DATA
TYPE OF SUBMISSIO	N N	TYPE	E OF ACTION
■ Notice of Intent		Abandonment	Change of Plans
Subsequent Benert		Recompletion	New Construction
Subsequent Report		Plugging Back	Non-Routine Fracturing
Final Abandonment Notice		Casing Repair	☐ Water Shut-Off
		Altering Casing	Conversion to Injection
		Other: Spud & csg report	
			(Note: Report results of multiple completion on Well Completion
Describe Proposed or Completed Operationally drilled, give subsurface locationally drilled. Spudded well	ions (Clearly state all per ions and measured and	rtinent details, and give pertinent dates, including es true vertical depths for all markers and zones pertine	Recompletion Report and Log Form.) stimated date of starting any proposed work. If well is ent to this work.)
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19	le. Ran 6 joints 9 collar 243.77'. C	9-5/8", 36#, K-55 8RD casing. Total cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ 0	le. Ran 6 joints 9 collar 243.77'. C9 bbls of F/W. Mt 07:00 p.m. on 05/	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ C closed csg @ sur	le. Ran 6 joints 9 collar 243.77'. Collar 243.77'. Collar 243.77'. Mile 107:00 p.m. on 05/rface. Tested OK	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ C closed csg @ sur	le. Ran 6 joints 9 collar 243.77'. Collar 243.77'. Collar 243.77'. Mile 107:00 p.m. on 05/rface. Tested OK	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	stimated date of starting any proposed work. If well is ent to this work.) footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake.
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ Colosed csg @ sur	le. Ran 6 joints 9 collar 243.77'. Collar 243.77'. Collar 243.77'. Mt. 07:00 p.m. on 05/rface. Tested OK	9-5/8", 36#, K-55 8RD casing. Total cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be to 1100 psi. cement to surface.	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ Colosed csg @ sur 4. Thereby certify that the foregoing is true a	le. Ran 6 joints 9 collar 243.77'. Collar 243.	9-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
directionally drilled, give subsurface location of the control of	le. Ran 6 joints 9 collar 243.77'. Collar 243.	9-5/8", 36#, K-55 8RD casing. Total cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be to 1100 psi. cement to surface.	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ Colosed csg @ sur 4. Thereby certify that the foregoing is true a SIGNED Sylvan. (This space for Federal or State office)	le. Ran 6 joints 9 collar 243.77'. Collar 243.	2-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be to 1100 psi. cement to surface.	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
directionally drilled, give subsurface location of the control of	le. Ran 6 joints 9 collar 243.77'. Collar 243.	9-5/8", 36#, K-55 8RD casing. Total cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be to 1100 psi. cement to surface.	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,
05/19/98 Spudded well 05/19/98 Drilled surface hole 289.45', depth of Displaced with 19 Bumped plug @ Colosed csg @ sur 4. I hereby certify that the foregoing is true a SIGNED Sylvan. (This space for Federal or State office)	le. Ran 6 joints 9 collar 243.77'. Collar 243.	2-5/8", 36#, K-55 8RD casing. Total Cement with 200 sxs. Class H w/ 3% uddy returns & cement returns @ 12/19/98 w/ 100 psi. Plug was down be to 1100 psi. cement to surface.	footage 276.45', depth of shoe CaCl2 & .25#/PPS Cello Flake. bbls, 88.17 sxs. Floats held. ut did not bump, float did not hold,