Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

RORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

	EMENT	5. LEASE DESIGNATION AND SERIAL NO.
	Committee of the second of the second of the second	SF 078972
SUNDRY NOTICES AND REP	PORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Do not use this form for proposals to drill or to dec		
	T-" for such people of the such	
		7. IF UNIT OR CA, AGREEMENT DESIGNATION
SUBMIT IN TRIPL	ICATE	
TYPE OF WELL	JUN 1 9 1988 L	8. WELL NAME AND NO.
OIL WELL GAS WELL OTHER		SAN JUAN 28-7 UNIT
NAME OF OPERATOR	ANG CAMP DIN	7 9. API WELL NO.
CONOCO INC.	Buch 9	#156M
ADDRESS AND TELEPHONE NO.	TOTAL 4500 (04E) 000 5404	10. FIELD AND POOL, OR EXPLORATORY AREA
10 Desta Drive, Suite. 100W Midland, Tex	as 79705-4500 (915) 686-5424	BLANCO MV/BASIN DAKOTA 11. COUNTY OR PARISH, STATE
LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Des 1045' FSL & 1890' FEL, UNIT LETTE		RIO ARRIBA COUNTY, NM
CHECK APPROPRIATE BOX(S)	TO INDICATE NATURE OF NOTICE	
TYPE OF SUBMISSION	TYPE	OF ACTION
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Water Shut-Off
	Altering Casing	Conversion to Injection
	Other: Spud & csg report	i i
	Dy Colai. Optic a con Toport	(hiote: Report results of multiple completion on Well Completion Recompletion Report and Log Form.)
3. Describe Proposed or Completed Operations (Clearly state all	pertinent details, and give pertinent dates, including e	
is directionally drilled, give subsurface locations and measured	and true vertical depths for all markers and zones pe	rtinent to this work.)
is directionally drilled, give subsurface locations and measured 05/19/98 Spudded well	l and true vertical depths for all markers and zones pe	rlinent to this work.)
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2	I and true vertical depths for all markers and zones pe LT&C casing. Total footage 3487, d Class H w/ 2% CaCl2 & .25#/PPS Co	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite.
o5/19/98 Spudded well o5/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/VV. Muddy slug @ 12:00 a.m. on 05/25/98 w/
o5/19/98 Spudded well o5/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy slug @ 12:00 a.m. on 05/25/98 w/
o5/19/98 Spudded well O5/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy slug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/VV. Muddy slug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/VV. Muddy slug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy slug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy slug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Colors, 16.2 sxs. Floats heki. Bumped p	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy lug @ 12:00 a.m. on 05/25/98 w/
o5/19/98 Spudded well o5/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Cel% CaCl2 and .25pps Cello-seal. Dis	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy lug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Colors, 16.2 sxs. Floats heki. Bumped p	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy lug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi. 4. I hereby certify that the foregoing is true and correct SIGNED SIGNED (This space for Federal or State office use)	LT&C casing. Total footage 3487, de Class H w/ 2% CaCl2 & .25#/PPS Colors, 16.2 sxs. Floats heki. Bumped p	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/VV. Muddy lug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, d. Class H w/ 2% CaCl2 & .25#/PPS Colors, 16.2 sxs. Floats heki. Bumped p	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/W. Muddy lug @ 12:00 a.m. on 05/25/98 w/
05/19/98 Spudded well 05/23/98 Ran 79 joints 7", 23#, K-55 8RD 3405.84'. Cement with 405 sxs. Followed by 50 sxs Class H w/ 2 returns & cement returns @ 6 bt 1500 psi.	LT&C casing. Total footage 3487, d. Class H w/ 2% CaCl2 & .25#/PPS Colors, 16.2 sxs. Floats heki. Bumped p	epth of shoe 3453', depth of collar ello-seal, 6.25pps Gilsonite. splaced with 134 bbls of F/VV. Muddy lug @ 12:00 a.m. on 05/25/98 w/

* See Instruction on Revenue Side

BY Est