

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NMNM-03547

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Breech "F" 1-F

9. API Well No.

30-039-25876-00X1

10. Field and Pool, or Exploratory Area

Basin Dakota, Tocito

11. County or Parish, State

Rio Arriba, New Mexico

SUBMIT IN TRIPLICATE

RECEIVED
AUG 6 1998

OIL CON. DIV.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Caulkins Oil Company

3. Address and Telephone No.

P.O. Box 340, Bloomfield, NM 87413

Ph. (505) 615-53

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1654' F/S 1526' F/W

Sec. 33-27N-6W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-28-98 Spud 12 1/4" hole at 3:15 a.m.

TD 12 1/4" surface hole at 463'.

Ran new 9 5/8" 36# J-55 seamless casing to 408' GL and cemented with 280 sacks (330 cu. ft.) class "B" cement with 2% CaCl and 1/4# per sack celloflake. Displaced 30 bbls H₂O.

Circulated 30 bbls cement to surface.

Shut down 12 hours, waiting on cement.

Tested surface casing with 1500# for 30 minutes.

Held OK.

NOTE: Hole bridged at 436' requiring surface casing to be cemented one joint shallower than originally planned. Both federal and state agencies were notified and approved surface casing depth. BLM authorized officer, Ron Snow, was on location and witnessed cementing procedure.

14. I hereby certify that the foregoing is true and correct

Signed Robert L. Vergue

Title Superintendent

Date July 29, 1998

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

AUG 03 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side