


State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well GAS</p> <p>2. Name of Operator <b>BURLINGTON RESOURCES</b> OIL &amp; GAS COMPANY</p> <p>3. Address &amp; Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <p>4. Location of Well, Footage, Sec., T, R, M 1820' FNL, 1585' FEL, Sec. 22, T-27-N, R-5-W, NMPM, Rio Arriba County</p>	<p>API # (assigned by OCD) 30-039-26258</p> <p>5. Lease Number Fee</p> <p>6. State Oil &amp; Gas Lease #</p> <p>7. Lease Name/Unit Name San Juan 27-5 Unit</p> <p>8. Well No. 156R</p> <p>9. Pool Name or Wildcat Tapacito Pict. Cliffs</p> <p>10. Elevation:</p>
---	---



Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

3-20-00 Drill to TD @ 3545'. Circ hole clean. TOOH. Drill pipe stuck @ 2003'.  
TIH w/free point to 1986'. Drill collar broke free @ 1921'. Circ hole  
clean above fish. TOOH. TIH w/fishing tools. Fishing.

3-21-00 Fishing.

3-22-00 (Verbal approval to plug and abandon, and skid rig from Frank Chavez, OCD).  
Back off drill string @ 1921'. TOOH w/fish & fishing tools. TIH, screw  
into fish @ 1921'. Circ hole clean. Establish injection. Plug #1: pump  
175 sx Class "B" neat cmt w/2% calcium chloride (207 cu.ft.) @ 2622-3545'.  
Displaced w/5 bbl wtr, 14 bbl mud. Squeeze to 600 psi. WOC. TOOH to 1721'.  
Plug #2: pump 50 sx Class "B" neat cmt w/2% calcium chloride (59 cu.ft.)  
@ 1721-1921'. Displace w/1 bbl wtr, 4 bbl mud. TOOH to 317'. Plug #3: pump  
75 sx Class "B" neat cmt w/2% calcium chloride (89 cu.ft.) @ 0-317'. Top  
off cmt w/15 sx Class "B" neat cmt. WOC. ND BOP. RD. Rig released.

SIGNATURE *Peggy Cole* Regulatory Supervisor March 23, 2000

no  
(This space for State Use)

NOV - 7 - 2000

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_