

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

2020' FSL, 2500' FWL, Sec. 22, T-27-N, R-4-W, NMPM

Lease Number
SF-080674

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-4 Unit
8. Well Name & Number
San Juan 27-4 U #149B
9. API Well No.
30-039-26267
10. Field and Pool
Blanco Mesaverde
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
0-300'	Spud	8.4-9.0	No control
300-3792'	LSND	8.4-9.0	No control
3792-6588'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
12 1/4"	0-300'	9 5/8"	32.3#	H-40
8 3/4"	0-3792'	7"	20.0#	J-55
6 1/4"	3692-6588'	4 1/2"	10.5#	J-55

Cementing Program:

9 5/8" surface casing - 239 sx Class "B" cement with 0.25 pps Flocele and 3% calcium chloride (282 cu.ft. of slurry, 200% excess to circulate to surface).
7" intermediate casing - lead w/403 sx Class "B" cement with 3% sodium metasilicate, 10 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 5 pps Gilsonite, 0.25 pps Flocele, 5 pps Gilsonite, 0.1% antifoam (1282 cu.ft. of slurry, 125% excess to circulate to surface).
4 1/2" production liner - cement with 295 sx Class "B" 50/50 poz w/4% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.3% fluid loss, 0.35% dispersant, 0.1% antifoam (487 cu.ft., 50% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Olthmann - for Title Regulatory Supervisor Date 8/10/00
no

(This space for Federal or State Office use)

APPROVED BY /s/ Jim Lovato Title _____ Date AUG 15 2000

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD