

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M


960' FSL, 1640' FWL, Sec. 23, T-27-N, R-4-W, NMPM

5. Lease Number
SF-080672

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-4 Unit
Well Name & Number
San Juan 27-4 U #32A
API Well No.
30-039-26378
Field and Pool
Blanco Mesaverde
County and State
Rio Arriba Co, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input checked="" type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well.

Revisions:

Mud Program:

Interval	Type	Weight	Fluid Loss
300-3808'	LSND	8.4-9.0	No control
3808-6597'	Air/Mist	n/a	n/a

Casing Program:

Hole Size	Depth Interval	Casing Size	Weight	Grade
8 3/4"	0-3808'	7"	20.0#	J-55
6 1/4"	3708-6597'	4 1/2"	10.5#	J-55

Cementing Program:

7" intermediate casing - lead w/356 sx Class "B" cement with 3% sodium metasilicate, 5 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/6% gel, 2% calcium chloride, 5 pps Gilsonite, 0.25 pps Flocele (1145 cu.ft. of slurry, 100% excess to circulate to surface).
4 1/2" production liner - cement with 294 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 0.1% retardant (415 cu.ft., 50% excess to circulate liner).

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (HGU) Title Regulatory Supervisor Date 6/15/00
no

(This space for Federal or State Office use)

APPROVED BY /s/ Jim Lovato Title _____ Date 6/21

CONDITION OF APPROVAL, if any: