

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 346-9700

4. Location of Well, Footage, Sec., T, R, M

500' FNL, 860' FEL, Sec. 10, T-27-N, R-4-W, NMPM

5. Lease Number
SF-080668

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-4 Unit
8. Well Name & Number
San Juan 27-4 U #140A
9. API Well No.
30-039-26457
10. Field and Pool
Blanco Mesaverde
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

8-14-00 Drill to intermediate TD @ 3790'. Circ hole clean. TOOH.

8-15-00 TIH w/5 jts 7" 23# N-80 LT&C csg, 80 jts 7" 20# J-55 ST&C csg, set @ 3783'. Pump 20 bbl wtr, 20 bbl mud flush, 20 bbl wtr ahead. Cmdt w/413 sx Class "B" cmt w/3% sodium metasilicate, 0.5 pps Cellophane, 10 pps Gilsonite, 0.1% defoamer (1198 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps Flocele, 5 pps Gilsonite, 2% sodium metasilicate (113 cu.ft.). Displace w/150.5 bbl wtr. Circ 80 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

8-19-00 Drill to TD @ 6775'. Circ hole clean.

8-20-00 TOOH. TIH w/156 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 6704'. Pump 10 bbl chemical wash, 2 bbl wtr ahead. Cmdt w/360 sx Class "B" 50/50 poz w/4% gel, 0.25 pps Cellophane, 5 pps Gilsonite, 0.3% fluid loss, 0.3% dispersant, 0.2% defoamer, 0.25% retardant (508 cu.ft.). Displace w/105.8 bbl wtr. WOC. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed
no

Title Regulatory Supervisor

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY

Title

Date

NOV 01 2000

CONDITION OF APPROVAL, if any:

FARMINGTON FIELD OFFICE