

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT"-for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PURE RESOURCES

3. Address and Telephone No.

P.O. BOX 850 - BLOOMFIELD, NM 87413

4. Location of Well (Footage, Sec., T., R., or Survey Description)

1402' FNL & 1913' FEL

"G" Sec 22, T27N, R07W

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 079360

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement Designation

RINCON UNIT

8. Well Name and No.

RINCON UNIT 185R

9. API Well No.

30-039-26690

10. Field and Pool, or Exploration Area

BASIN DK/BLANCO MV

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other

DRILLING

- ☐ Change of Plans  
☐ New Construction  
☐ Non-routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completions or Recompletions Reports and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)\*

SEE ATTACHED

2001 MAY 16 PM 2:27

14.

Signed

*Micheal C. Phillips*  
MICHEAL C. PHILLIPS

Title

SAN JUAN BASIN FOREMAN

Date

05/14/01

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Sections 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States of false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instructions on Reverse Side

NMOCD

3Y *SPM* OFFICE

**PURE RESOURCES, INC.**  
**DAILY DRILLING REPORT**

**RINCON UNIT #185R - 76.82% WI**

**Lease Well: 521508-0185**

**State: NM**

**County: RIO ARRIBA**

**4/15/2001** MIRU BEARCAT RIG #1, 04/14/01 11:55 P.M. DRLG RAT & MOUSEHOLES. DRLG 12-1/4" HOLE TO 70' W/ ALL WT, 80-100+ RPM, 400 PSI, 250 GPM.

**4/16/2001** DRLG F/ 70-389' W/ ALL WT, 80-100 RPM, 1000 PSI, 335 GPM, SPUD MUD. RUN 9 JTS 9-5/8" 32.3# STC SET @ 384'. TOP INSERT @ 342'. CMT W/ 250 SX "B" W/ 2% CACL2, .25 PPS CELLOFLAKE. CIRC 35 BBLS CMT. TEST CSG, BLIND RAMS, CHOKE & BOP TO 600 PSI.

**4/17/2001** DRLG CMT F/ 342-389. DRLG 8-3/4" HOLE F/ 389-2030' W/ 15-45K, 70-85 RPM, 1500 PSI, 336 GPM, POLY MUD -2030' W/ 40-45K, 80-85 RPM, 1500 PSI, 336 GPM, POLY MUD.

**4/18/2001** DRLG F/ 2030-2464' / 40-45K WT, 80 RPM, 1500 PSI, 336 GPM, POLY MUD. RUN 59 JTS (2459.45') 7" 20# K-55 STC CSG. SET @ 2459', TOP FC @ 2417'. PUMP 20 BBL MUD FLUSH, 10 BW, 325 SX LEAD @ 12.1 PPG. TAIL W/ 70 SX @ 14.6. DROP PLUG & DISP W/ 97.9 BW. CIRC 31 BBLS GOOD CMT TO PIT.

**4/19/2001** TEST CSG, CHOKE & BOP, BLIND RAMS TO 1500 PSI. PU HAMMER, (10) 4-3/4" DC'S & 3-1/2" DP. TIH TO 2410', TAG CMT. TEST CSG, CHOKE & BOP, PIPE RAMS TO 1500 PSI. DRLG CMT, PLUG, FC, CMT & SHOE. DRLG F/ 2464-3480' W/ 2-4K, 40 RPM, 400 PSI AIR, 2050 SCFM.

**4/20/2001** DRLG F/ 3480-5700' W/ 2-4K, 40 RPM, 2050 SCFM, 500 PSI.

**4/21/2001** DRLG F/ 5700-6429' W/ 2-4K, 40 RPM, 2050 SCFM, 450 PSI. XO TO N2. DRLG F/ 6429-7067' W/ 2-4K, 40 RPM, 100-1300 SCFM N2.

**4/22/2001** DRLG F/ 7067-7533' W/ 2-4K, 40 RPM, 1050 SCFM N2, 300 PSI.

**4/23/2001** RAN 179 JTS (7539') 4 1/2" 11.6# I-80 LTC csg. SET @ 7532'. TOP FC @ 7489'. PUMP 20 BBLS CHEMICAL WASH, 10 BW LEAD W/ 85 SX (201 FT3) @ 11.9 PPG. TAIL W/ 525 SX PREM LITE HIGH STRENGTH "F" @ 12.5 PPG @ 5 BPM, 255 PSI. DROP PLUG & DISPLACE W/ 116.2 BW @ 5 - 2.5 BPM. MAX LIFT 1845 PSI. BUMP PLUG TO 2400 PSI. CIRC 25 BBLS GOOD CMT TO PIT. SET SLIPS W/ 77K#. CUT OFF 18' 4-1/2" CSG. RIG RELEASED @ 9:00 PM 4/22/01.

---