Form 3160-5 (August 1999)

UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS				Jicarilla Contract 94	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side			7. k(Unit or CA/Agreement, Name and/or N 21937		
1. Type of Well Oil Well X Gas Well Other 2. Name of Operator ENERGEN RESOURCES CORPORATION 3a. Address 2198 Bloomfield Highway, Farmington, NM 87401 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2400' FSL, 1650' FEL, Sec.22, T27N, R03W, N.M.P.M.		3b. Phone No. (include area code) 505-325-6800		8. Well Name and No. Jicarilla 94 1C 9. API Well No. 30-039-26853 10. Field and Pool, or Exploratory Area Blanco Mesaverde 11. County or Parish, State Rio Arriba NM	
12. CHECK APPROPRIATE	BOX(ES) TO INDI	CATE NATURE OF N	OTICE, REP		
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent X Subsequent Report Final Abandonment Notice 13. Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. I	plete horizontally, give sub formed or provide the Bo of the operation results in	, including estimated startin ssurface locations and meast and No. on file with BLM/la a multiple completion or re-	Reclamatic Recomplet Temporari Water Disp g date of any proured and true ver BIA. Required s	ly Abandon posal posed work and appritical depths of all persubsequent reports show hew interval, a Form	rtinent markers and zones all be filed within 30 days 3160-4 shall be filed once
testing has been completed. Final Abandonment Netermined that the final site is ready for final inspector. O2/05/02 TD: 6549'. Ran 55 jts. RU Halliburton. Cement with 270 2% gel, 0.5% Halad-9, 0.2% CFR-3, Circulate 10 sks cement to surface 6:00 am 02/06/02.	4-1/2" 10.5# J-5 sks of 50/50 Clas 0.1% HR-5 (356 ct	55 ST&C casing, se ss B poz, 5#/sk gi u.ft.). Plug down	t @ 6525'. lsonite, 1/ @ 10:30 pm	TOL: 4203'. /4#/sk flocele n on 02/05/02. Released rig @	

I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title
Vicki Donaghey	Production Assistant
Vicki Donastar	Date 02/07/02
HIS SPACE FOR	R FEDERAL OR STATE OFFICE USE
Approved by /s/ Erian M. Erwio	Lahds and Mineral Resources Date FEB 2 2 2002
Conditions of approval, if any, are attached. Approval of this notice does certify that the applicant holds legal or equitable title to those rights in t which would entitle the applicant to conduct operations thereon.	