| | For: | m. 9-: pril 19 | 8 81 b (52) | |
|---|------|-------------------|-----------------------|--|
| | | | | |
| | | | • | |
| | | | | |
| i | | | | |

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| Indian Agency Jicarill | a |
|------------------------|---|
| | / |
| Allettee | |
| oase No237 | |

| NOTICE OF INTENTION TO DRILL | | |
|--|--|---|
| NOTICE OF INTENTION TO CHANGE PLA | ANC | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO TEST WATER | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZANG |
| NOTICE OF INTENTION TO REDRILL OR | 1 | SUBSEQUENT REPORT OF REDRILLING OR REPAIR 111N 4 1962 |
| NOTICE OF INTENTION TO SHOOT OR A | 1, | THE STATE OF REPAIR |
| NOTICE OF INTENTION TO PULL OR AL | 1 1 | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO ABANDON W | i I | SUPPLEMENTARY WELL HISTORY. U. S. GEOL CONCAL SU |
| (INDICATE | ABOVE BY CHECK MARK NATU | JRE OF REPORT, NOTICE, OR OTHER DATA) |
| | • | |
| | - | May 28 , 19 62 |
| NE. (34 Sec. and Sec. No.) | | mge) (Meridian) |
| Puerto Chiquito | Kio Arriba (County or Sub | a New Mexico. |
| ate names of and expected depths to ol | | OF WORK ights, and lengths of proposed casings; indicate mudding jobs, cement- important proposed work) |
| Drilled 9 5/8 hold Drilled 0 3/4 hold Drilled 4 3/4 hold Formation Packer 3 | e to 809! and e to 1074! | |
| Drilled 9 5/8 hold Drilled 0 3/4 hold Drilled 4 3/4 hold Formation Packer : No water GTSM. | e and set 40° e to 809° and e to 1674° and Shoe at 1650°. | of 7 5/8" casing w/25 sax. set 5 1/2 casing w/40 sax. d ran 2 7/8 EUE tubing w/Halliburton. Potentialed for 11 BUPD - |
| Drilled 9 5/8 hold Drilled 0 3/4 hold Drilled 4 3/4 hold Formation Packer : No water GTSM. | e and set 40° e to 809° and e to 1674° and Shoe at 1650°. | of 7 5/8" casing w/25 sax. set 5 1/2 casing w/40 sax. d ran 2 7/8 EUE tubing w/Halliburton. Potentialed for 11 BUPD - |
| Drilled 9 5/8 hold Drilled 0 3/4 hold Drilled 4 3/4 hold Formation Packer 3 No water GTSM. | e and set 40° e to 809° and e to 1674° and Shoe at 1650°. | of 7 5/8" casing w/25 sax. set 5 1/2 casing w/40 sax. d ran 2 7/8 EUE tubing w/Halliburton |
| Drilled 9 5/8 hold Drilled 0 3/4 hold Drilled 4 3/4 hold Formation Packer : No water GTSM. | e and set 40° e to 809° and e to 1674° and Shoe at 1650°. | of 7 5/8" casing w/25 sax. set 5 1/2 casing w/40 sax. d ran 2 7/8 EUE tubing w/Halliburton. Potentialed for 11 BUPD - |