


(SUBMIT IN TRIPLICATE)



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Survey: Survey 200
Allottee: Survey 200
Lease No. 14-02-402-341

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	XX
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Robta, New Mexico - October 22, 1962

Well No. Survey 200 is located 700 ft. from S line and 1450 ft. from W line of sec. 34

Sec. 34 (34 Sec. and Sec. No.) 24-N (Twp.) 14-W (Range) N.M.P.M. (Meridian)
W. 14-02-402-341 (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6262 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded August 15, 1962. Set 10-3/4" OD casing at 1246' and cemented with 700 sacks. Cement circulated to surface. Plug down at 12:25 P.M. August 21, 1962. U.O.S. 24 hours. Shut off tested OK. Reached total depth of 11,822' on October 6, 1962. No commercial quantities of oil or gas was encountered in any zone of this well. The well was plugged and abandoned according to the Rules and Regulations of the New Mexico Oil Conservation Commission and the United States Geological Survey.

Spotted cement plugs as follows:

11,822' - 10,823' - 100 sacks cement
10,775' - 10,675' - 95 sacks cement

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be conducted.

Company Shelly Oil Company

Address P. O. Box 38

Robta, New Mexico

By (original) H. E. Aub

Title Dist. Supt.

RECEIVED
OCT 31 1962

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

RECEIVED
NOV 1 1962
(See November 1962)
OIL CON. COM.
DIST. 3

9,900' - 9,800'	- 55 sacks cement
8,325' - 8,225'	- 55 sacks cement
6,900' - 6,800'	- 55 sacks cement
5,700' - 5,600'	- 55 sacks cement
4,900' - 4,800'	- 55 sacks cement
2,750' - 2,603'	- 100 sacks cement
1,450' - 1,300'	- 75 sacks cement
TOTAL	605 sacks cement

Ran 15 sacks cement cap and installed 4" pipe marker. All intervals not filled with cement plug were filled with heavy mud laden fluid. Plugging operations were completed on October 16, 1962.

Verbal approval to plug and abandon this well was secured from Mr. Richard Krahl.