



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 14-08-0001-6890
Unit West Risti Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 10, 1963, 19__

Well No. 22 is located 1980 ft. from N line and 1980 ft. from E line of sec. 34

C SW NE 34
(1/4 Sec. and Sec. No.)

26N
(Twp.)

13W
(Range)

10MPM
(Meridian)

Risti Gallup
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6270 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-9-63

Rigged up Halliburton to frac. Loaded hole and broke down with 100 EO at 1500 psi. Mixed 15,000# sand in 15,000 gallons oil. Mixed 500# phosphate in last 3,000 gallons. Cut off sand and displaced with 20 barrels oil. Dropped 25 bridging balls. Mixed 15,000# sand in 15,000 gallons oil. Mixed 500# phosphate in last 3,000 gallons. Flushed with 150 barrels oil. Average injection rate 36 BPM at 1600#. 5 minute shut in pressure 800#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Producing Co.

Address P. O. Drawer 330

Farmington, N.M.

By Nae R. Stone
Title Field Superintendent

