

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078091

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 141

9. API Well No.

30-045-05649

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL - 1980' FEL
Sec. 28, T26N, R13W, NMPM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug well as follows:

1. Set cast iron bridge plug at Gallup top (4968') and spot 50' Class B cement plug to top of plug.
2. Perforate 50' below Mesa Verde top (2151') and spot 100' Class B cement plug plus excess inside and outside casing.
3. Perforate 50' below Pictured Cliffs top (1417') and spot Class B + 4% gel plug to cover Fruitland top (1182').
4. Perforate 50' below surface casing (214') and circulate Class B + 4% gel to surface.

Water will be used to spot all plugs as permitted on other wells in this area.

Class B = 15.6 lb./gal.; 1.18 cu. ft./sk.

Class B + 4% gel = 14.1 lb./gal.; 1.55 cu. ft./sk.

RECEIVED
MAY 23 1994

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed John Alexander

Title Operations Manager

Date 5/10/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED
AS AMENDED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

DISTRICT MANAGER