

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	New	Mexico	
Lease No.			
Unit			

SUNDRY NOTICES AND REPORTS ON WELLS

	SOUDK! HOIL			
	TENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
	TENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
	TENTION TO CHANGE FLANS		SUBSEQUENT REPORT OF ALTERING CASING	
	TENTION TO RE-DRILL OR REPAIR W		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.	
	TENTION TO RE-DRILL OR REPAIR I		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INT	TENTION TO SHOOT OR ACTURED TENTION TO PULL OR ALTER CASING	=	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INT	TENTION TO PULL OR ALTER CASING	J		
NOTICE OF INT	TENTION TO ABANDON WELL			
	(INDICATE ABOVE BY	CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)	(1.212)
			April 24,	1 9 62
			April 21,	
S Vell No.	anger 1-26 is located 930	0_ft.from_{	$\left\{ egin{array}{c} \mathbb{N} \\ \mathbb{N} \end{array} \right\} \ \text{line and} \ \left\{ egin{array}{c} \mathbb{N} \\ \mathbb{N} \end{array} \right\} \ \text{line}$	of sec. 26
SE	26 26	N 81		
(1/4 Sec.	and Sec. No.) (Tw	= -	NT) (i o	
Ballard	Pictured Cliffs	San Juan	New Mexic (State or Territor	
	(Field)	(County or Su	bdivision) (Ballo of Tottilor	3,
he elevatio	on of the derrick floor abo	ove sea level	; 7000 f+ KB	
	Oli Ol the deliter mean and	010 000 10101	15 111111111111111111111111111111111111	
	on of the definer neer as			
		DETAILS	OF WORK	udding jobs, coment-
State names of	and expected depths to objective sa ing po	DETAILS ands; show sizes, v pints, and all other	OF WORK veights, and lengths of proposed casings; indicate m r important proposed work)	
Drilled regular 1500#,	to 2945' KB. Ran 4.4% gel cement. Pl	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK weights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus SI, held OK.	226 sx.
Drilled regular 1500#,	to 2945' KB. Ran 4. 4% gel cement. Pl	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK reights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus 5I, held OK.	226 sx.
Drilled regular 1500#,	to 2945' KB. Ran 4. 4% gel cement. Pl	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK reights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus 5I, held OK.	226 sx.
Drilled regular 1500#,	to 2945' KB. Ran 4.4% gel cement. Pl	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK reights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus 5I, held OK.	226 sx.
Drilled regular 1500#,	to 2945' KB. Ran 4 4% gel cement. Pl float held. Tested	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK veights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus 5I, held OK.	226 sx.
Drilled regular 1500#,	to 2945' KB. Ran 4. 4% gel cement. Pl float held. Tested Consolidated Oil & 2112 Tower Buildi	DETAILS ands; show sizes, voints, and all other 4 1/2" 16. lug down 6 to 2000 PS	OF WORK reights, and lengths of proposed casings; indicate me important proposed work) 6# drill pipe cemented with 2 a.m. 3/30/62. Bumped plus 5I, held OK.	226 sx.