

(SUBMIT IN TRIPLICATE)


UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Navajo Indian

Allottee _____

Lease No. **14-20-603-773**



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 7, 1963, 19__

J. Glenn Turner - Juan Jones

Well No. **1-30** is located **1,480** ft. from **S** line and **790** ft. from **W** line of sec. **30**

SW/4 Section 30
(1/4 Sec. and Sec. No.)

T 26-North R 8-West
(Twp.) (Range)

N.M.P.M.
(Meridian)

Basin Dakota
(Field)

San Juan County
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **6,269** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Basin Dakota test. West half Section 30 (320 Acres) dedicated to this well.

Casing program: Set 300 feet of 8-5/8" 24# J-55 casing with 200 sacks 1/2 gal cement. Circulate cement to surface.

Drill with rotary rig to approximately 6800 feet, and set 4-1/2" or 3-1/2" casing with 200 sacks, 1/2 gal cement.

Stage collar will be set approximately 100 feet below Pictured Cliffs formation - and that formation will be cemented with approximately 50 sacks 1/2 gal cement.

If commercial production indicated, formation will be sand water fractured through perforations, and tubing will be set for production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **J. Glenn Turner**

Address **P. O. Box 728**

Farmington, New Mexico

By

Title **G. Deason Paul, Agent in Farmington**