

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 07809/
NM 013492-1

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Gulf Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 1980' FNL

RECEIVED
NOV 08 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

7. UNIT AGREEMENT NAME

West Bisti Unit

8. FARM OR LEASE NAME

9. WELL NO.

127

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 28-T26N-R13W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6263' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Repair Casing Leak

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

POH with production equipment. Set RBP at 4950', cap with 10' sand. Locate casing leak. Set cement retainer 75' above casing leak. Cement as necessary. Drill cement and cement retainer. Test squeeze 500#. Reverse sand off RBP and POH. RIH with production equipment, hang off.



18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. Pitts

TITLE

Area Engineer

DATE

11-5-82

(This space for F. A. M. F. S. M. use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

NOV 09 1982

AMES F. SIM
DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side