

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078092
Unit Gov. Douthit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Set Production Casing</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


July 16, 1957

Douthit
Well No. B-16 is located 660 ft. from N line and 660 ft. from E line of sec. 28
6-NE NE Section 28 26N 13W New Mexico P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Bisti-Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)
ground level
The elevation of the ~~derrick~~ above sea level is 6257.8 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Drilled to 5178' KB. TD. Conditioned hole and ran 138 joints 5-1/2" OD, 14#, J-55 Sals. Casing, equipped with centralizers, scratchers and Baker float equipment. Casing landed at 5176' KB and cemented with 200 sac 3/4 Gal Cement. Displaced to 5106' KB under 1500 pounds psi. Ran Temperature Survey, found top of cement at 4600' KB.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Producing Company
Address Box 180
Denver 1,
Colorado
Original Signed by J. E. Stein
By _____
Title District Engineer

