

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SF 078091

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 122

9. API Well No.

30-045-05711

10. Field and Pool, or Exploratory Area

*Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well☐ Gas Well☒ Other

Water Injection Well*

P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

840' FNL - 975' FEL

Sec. 29, T26N, R13W, NMPM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☐ Recombination☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Spot 74 cu. ft. class "B" cement with 2% CaCl₂ @ 5153'. Tag cement @ 4804'. Gallup plug 4804' - 5153'.
2. Perforate 5½" casing @ 2298'. Spot 63 cu. ft. class "B" cement @ 2326'. Displace cement to 2148'. Mesa Verde plug 2148' - 2298'.
3. Perforate 5½" casing @ 1554'. Spot 143 cu. ft. class "B" cement with 4% gel @ 1573'. Displace cement to 1113'. Fruitland - Pictured Cliffs plug 1113' - 1554'.
4. Perforate 5½" casing @ 384'. Est. circulation out bradenhead. Fill 5½" casing and 5½" - 9-5/8" annulus with 239 cu. ft. class "B" cement with 4% gel. Surface - Ojo Alamo plug 0' - 384'.

Job complete 5/26/95.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

Date

6/6/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

JUN 8 1995
DISTRICT MANAGER