Form 3160-5 UNITED STATES PORM APPROVED (June 1990) DEPARTMENT OF THE INTERIOR Budget Burese No. 1004-0135 Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Serial No. SF 078091 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agrocopent Designation SUBMIT IN TRIPLICATE 1. Type of Well West Bisti Unit W Well Gas Well P&A Other 8. Well Name and No. 2. Name of Operator West Bisti Unit 123 Dugan Production Corp. 9. API Well No. 3. Address and Telephone No. 30-045-05712 P.O. Box 420, Farmington, NM 87499 10. Field and Pool, or Exploratory Area (505) 325-1821 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Bisti Lower Gallup 660' FNL - 1980' FWL 11. County or Parish, State Sec. 28, T26N, R13W, NMPM San Juan, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Change of Plans Recompletion **New Construction** Plugging Back Non-Routine Fracturing 6 1994 Casing Repair Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multi all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly) give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)* Plugged well as follows: Spot 59 cu. ft. class "8" with 3% CaCl₂. Tag cement 8 5136'. Spot 59 cu. ft. class "8" w/3% CaCl₂. Found hole in tubing. Ran tubing to 4806'. Pressure test tubing to 1000 psi. Spot 59 cu. ft. class "B" w/3% CaCl₂. Tag cement 4487'. Gallup plug 4487' - 4806'.
Perforate 5% casing 8 2170'. Spot 59 cu. ft. class "B" neat cement. Displace cement to 2025'. Hesa Verde plug 2025 - 2170 . Perforate casing at 1460'. Spot 166 cu. ft. class "B" cement with 4% gel. Displace 1% bbl cement. Locked up 8 100) psi. Pictured Cliffs - Fruitland plug 270' - 1460' (inside casing).* Perforate 51/4 cusing 8 3481. Cement 51/4 casing & surface pipe to surface with 166 cm. ft. cement w/4% gel. * Calculated top of cement above depth of surface plug perforation. BLM representative approved all changes. Job complete 10-13-94. Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed. ထ Operations Manager 10/17/94 Date (This space for Federal or State office use) Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Section 1001. or representations as to any matter within its jurisdiction.