

(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Land Office	Mov	Mexico
ease No.	0901	IÚ
Jnit	ACC U	mell

NOTICE OF INTENTION TO DRILL	AND REPORTS ON WELLS
HOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
MOTICE OF INTENTION TO TEST WATER SHIT OFF	SECOND REPORT OF SHOOTING OR ACIDIZING
HOTICE OF INTENTION TO RE-DRILL OR DEDATE	REPORT OF ALTERING CASING
MOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ABANDON WELL	SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	THE OF REPORT, NOTICE, OR OTHER DATA)
	Jane 11 19 5
Well No. is located ft. from	19.2
Si Section 24	S line and the ft. from W line of sec.
(1/2 Sec. and Sec. No.) (Twp.)	The Name of the Control of the Contr
Fallard P.C.	(Range) (Meridian)
(Field) (County	or Subdivision)
he elevation of the derrick floor above sea le	vel is 😘 👍
tate names of and expected depths.	ILS OF WORK
ing points, and all o	es, weights, and lengths of proposed casings: indicate
7 ma - 2	LS OF WORK es, weights, and lengths of proposed casings; indicate mudding jobs, cement ther important proposed work)
3-23-56. Total Deuth 2058.	es, weights, and lengths of proposed casings; indicate mudding jobs, cement ther important proposed work)
3-23-56. Rotal Depth 2058.	
3-23-56. Total Depth 2058. Ban 66 Joints 5 1/2", 15.50\$, J-55 cocks regular conect. 75	
3-23-56. Rotal Depth 2058. San 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Potal Depth 2058. San 56 Joints 5 1/2", 15.50%, J-55 c macks regular cement, 75 eachs Pount sald 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Rotal Depth 2058. Rem 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Rotal Depth 2058. Rem 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Rotal Depth 2058. Rem 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Rotal Depth 2058. Rem 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-23-56. Rotal Depth 2058. Rem 56 joints 5 1/2", 15.50%, J-55 c sacks regular cement, 75 eachs Pount Salé 1000/ for 30 minutes	meths (20k8') set at 2058' with 75
3-83-56. Total Depth 2058. Ren 56 joints 5 1/2", 15.50%, J-55 conche regular cement, 75 sacks Possible 1000% for 30 minutes. Rop of cement by temperature survey in the content by temperature survey.	main; (20k8') set at 2058' with 75 m. 4% Gel. at 1140'.
3-83-56. Total Depth 2058. Ren 56 joints 5 1/2", 15.50%, J-55 conche regular cement, 75 sacks Possible 1000% for 30 minutes. Rop of cement by temperature survey in the content by temperature survey.	main; (20k8') set at 2058' with 75 m. 4% Gel. at 1140'.
Jest Sold Lepth 2098. See Sold Lepth 2098. Seeks regular canent, 75 sacks Possifuld 1000/ for 30 simulate. The of occupant by temperature survey of occupant by the occ	meths (20k8') set at 2058' with 75
understand that this plan of work must receive approval in wr	main; (20k8') set at 2058' with 75 m. 4% Gel. at 1140'.
Hen 6 joints 5 1/2", 15.50, 1-55 cocks regular coment, 75 macks Possilizated 1000/ for 30 minutes. The of coment by temperature purvey in writing the content by temperature purvey in the content by temperature purvey in the content by temperature purvey. The content by temperature purvey in the content by temperature purvey.	main; (20k8') set at 2058' with 75 m. 4% Gel. at 1140'.
See to joints 5 1/2", 15.50%, 1-55 codes regular cement, 75 modes Possitions. The of cement by temperature survey with the code of cement by temperature survey with the code of cement by temperature survey. The of cement by temperature survey with the code of cement by temperature survey.	main; (20k8') set at 2058' with 75 m. 4% Gel. at 1140'.
understand that this plan of work must receive approval in wr mpany El Page Schurzel Cas Company lices Box 997	at 1140'.