

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL - 1980' FWL
Sec. 20, T26N, R13W, NMPM

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 013492

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 110

9. API Well No.

30-045-05745

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Set cast iron bridge plug at 5241'.
2. Spot 19 cu. ft. Class B cement @ 5241'. Gallup plug 5102' - 5241'.
3. Perforate casing @ 2422'. Spot 59 cu. ft. Class B cement @ 2433'. Displace cement to 1838' and pressured up. Mesa Verde plug 1838' - 2422'.
4. Perforate casing @ 1643'. Spot 202 cu. ft. Class B + 4% gel cement @ 1653'. Displace cement to 1193'. Pictured Cliffs - Fruitland plug 1193' - 1643'.
5. Perforate casing @ 510'. Pump down casing and was unable to establish circulation to surface. Pumped 59 cu. ft. class "B" cement down casing and displaced to 360'. Ojo Alamo plug 360' - 510'.
6. Perforated casing @ 245'. Pumped 214 cu. ft. Class B + 4% gel cement down casing and circulated to surface. *

* Changes made with concurrence of BLM representative.
Job complete 10-18-94.Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

Date

10/20/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED

OCT 21 1994

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side