DEPUTY OIL & GAS INSPECTOR

DEC 2 9 1997

Meter Number:74618
Location Name:HUERFANO UNIT #93
Location:TN-26 RG-09
SC-22 UL-D
2 - Federal
NMOCD Zone:OUTSIDE

DECEIVE N APR 1 4 1997

VID (100). DIV. Bibil 3

#### RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

Hazard Ranking Score:00

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone  $10^{-9}$  to  $10^{-13}$  cm/sec Shale  $10^{-12}$  to  $10^{-16}$  cm/sec Clay  $10^{-12}$  to  $10^{-15}$  cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.



### FIELD PIT SITE ASSESSMENT FORM

| 4               |   |  |  |  |  |  |  |
|-----------------|---|--|--|--|--|--|--|
| GENERAL         | Meter: 74618 Location: Herrano No. 93  Operator #: 2999 Operator Name: Merrano P/L District: Ballaca  Coordinates: Letter: D_ Section 22 Township: 26NRange: 9W  Or Latitude Longitude  Pit Type: Dehydrator Location Drip: X Line Drip: Other:  Site Assessment Date: 6-20-94 Area: 11 Run: 91   |  |  |  |  |  |  |
| SITE ASSESSMENT | NMOCD Zone:       Land Type:       BLM       □ (1)         (From NMOCD       State       □ (2)         Maps)       Inside       □ (1)       Fee       □ (3)         Outside       □ (2)       Indian       □         Depth to Groundwater       □ (1)       □ (1)         Less Than 50 Feet (20 points)       □ (1)       □ (2)         Contact That 100 Ft (2)       □ (2) |  |  |  |  |  |  |
|                 | Greater Than 100 Ft (0 points) (3)  Wellhead Protection Area:  Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? (1) YES (20 points) (2) NO (0 points)   |  |  |  |  |  |  |
|                 | Horizontal Distance to Surface Water Body  Less Than 200 Ft (20 points) ☐ (1)  200 Ft to 1000 Ft (10 points) ☐ (2)  Greater Than 1000 Ft (0 points) ☒ (3)  Name of Surface Water Body  (Surface Water Body : Perennial Rivers, Major Wash, Streams, Creeks, Irrigation Canals, Ditches, Lakes, Ponds)  Distance to Nearest Ephemeral Stream ☐ (1) < 100'(Navajo Pits Only)  |  |  |  |  |  |  |
|                 | TOTAL HAZARD RANKING SCORE: $\bigcirc$ POINTS   |  |  |  |  |  |  |
| KS              | Remarks: One Piton location. Dry  |  |  |  |  |  |  |
| REMARKS         | Outside V.Z. on Topo  |  |  |  |  |  |  |
|                 | Inside V.Z. on Redline Pask In  |  |  |  |  |  |  |

Date

Signature

## FIEL PIT REMEDIATION/CLOSULE FORM

| GENERAL            | Meter: 74618 Location: Hver from #93  Coordinates: Letter: D Section 22 Township: 26 Range: 9  Or Latitude Longitude ——  Date Started: 9.29-94 Run: 11 91                                  |
|--------------------|--|
| FIELD OBSERVATIONS | Sample Number(s): $\frac{12!}{2}$ Feet  Final PID Reading $\frac{1}{2}$ PID Reading Depth $\frac{12!}{2}$ Feet  Yes No  Groundwater Encountered $\square$ Approximate Depth $\square$ Feet |
| CLOSURE            | Remediation Method:  Excavation  |
| REMARKS            | Remarks: 10 yels F:11  Signature of Specialist: Walk Wilson  |



# FIELD SERVICES LABORATORY ANALYTICAL REPORT

## PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

### SAMPLE IDENTIFICATION

|                            | Field ID |       |            | Lab ID          |      |         |   |  |
|----------------------------|----------|-------|------------|-----------------|------|---------|---|--|
| SAMPLE NUMBER:             | MBER:    |       | 946266     |                 |      |         |   |  |
| MTR CODE   SITE NAME:      | 74618    |       |            | N/A             |      |         |   |  |
| SAMPLE DATE   TIME (Hrs):  |          |       | 1245       |                 |      |         |   |  |
| SAMPLED BY:                |          | /A    |            |                 |      |         |   |  |
| DATE OF TPH EXT.   ANAL.:  | 10-3-94  |       |            |                 |      |         |   |  |
| DATE OF BTEX EXT.   ANAL.: | 414      |       |            | NIA             |      |         |   |  |
| TYPE   DESCRIPTION:        |          |       | Prozer 1 - | Brown fine Sand |      |         |   |  |
| RESULTS                    |          |       |            |                 |      |         |   |  |
|                            |          |       |            |                 |      | <u></u> | 1 |  |
| PARAMETER                  | RESULT   | UNITS |            | N/ 0            | 1    |         |   |  |
|                            |          |       | DF         | <u> </u>        | M(g) | V(ml)   | 1 |  |
| TPH (418.1)                | 36.5     | MG/KG |            |                 | 2.01 | 28      |   |  |
| HEADSPACE PID              |          | PPM   |            |                 |      |         |   |  |
|                            | 0117     |       |            |                 |      |         | I |  |

| PERCENT SOLIDS           | 94.7 | %                    |       |  |  |
|--------------------------|------|----------------------|-------|--|--|
|                          |      | TPH is by EPA Method | 418.1 |  |  |
| larrative:               |      |                      |       |  |  |
|                          |      |                      |       |  |  |
| F = Dilution Factor Used |      |                      |       |  |  |
|                          |      |                      |       |  |  |
|                          |      |                      |       |  |  |
|                          |      |                      |       |  |  |

\*\*\*\*\*\*\*\*\*\*\*\* Test Method for Oil and Grease and Petroleum Hydrocarbons in Water and Soil

Perkin-Elmer Model 1600 FT-IR

Analysis Report \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

94/10/03 14:56

Sample identification 246266

Tribial mass of sample, g

Volume of sample after extraction, ml 18.000

Petroleum hydrocarbons, ppm 76.469

Nel absorbance of hydrocarbons (2930 cm-1)

