

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED
NOV 27 1995
P&A

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Injection Well *

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL - 1980' FEL
Sec. 19, T26N, R13W, NMPM

5. Lease Designation and Serial No.

NM 013492

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 107

9. API Well No.

30-045-05794

10. Field and Pool, or Exploratory Area

*Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Set cast iron bridge plug @ 5197'.
2. Spot 12 cu. ft. class "B" cement on top of plug. Gallup plug 5110' - 5197'.
3. Perforate 5½" casing @ 2448'.
4. Spot 59 cu. ft. class "B" cement @ 2473'. Displace cement to 2298'. Mesa Verde plug 2298' - 2448'.
5. Perforate casing @ 1735'.
6. Spot 202 cu. ft. class "B" cement with 4% gel @ 1753. Displace cement to 1250'. Pictured Cliffs - Fruitland plug 1250' - 1753'.
7. Perforate 5½" casing @ 504'.
8. Circulate cement to surface with 251 cu. ft. class "B" cement with 4% gel. Surface plug 0' - 504'.

Job complete 11/14/95.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander Title Operations Manager Date 11/17/95

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

DISTRICT MANAGER