

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection Well		5. LEASE DESIGNATION AND SERIAL NO.	
2. NAME OF OPERATOR Shelly Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Tribal 14-20-603-294	
3. ADDRESS OF OPERATOR 1500 Lincoln Street - Denver, Colorado 80203		7. UNIT AGREEMENT NAME Collapsa Collaps Sand Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FML & 1980' FML of Section 11-26N-12W		8. FARM OR LEASE NAME	
14. PERMIT NO.		9. WELL NO. 40	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3951' GR		10. FIELD AND POOL, OR WILDCAT Collapsa Saline	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 11-26N-12W	
		12. COUNTY OR PARISH SAN JUAN	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

February 5, 1968, moved in and rigged up pulling unit. Squeezed perforations 5108-5140' with 15 sacks of cement, 3% gel. Estimated top of plug at 4490'. Rigged up jacks. Worked casing to 150,000#. Found free point at 1250'. Shot 5-1/2" OD casing at 1157'. Pulled 37 joints (1256') of 5-1/2" OD. 148. 3-55, 1-2, condition "C" casing. Plugged as follows:

20 sacks of cement - 1207-1307'

20 sacks of cement - 650- 550'

Set 10 sack cement plug in top of surface casing with dry hole marker.

Completed P & A February 8, 1968.

RECEIVED

FEB 11 1968

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Leland H. Hargis*TITLE **District Superintendent**DATE **Feb. 12, 1968**

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.