MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

For	m C-122
Revised :	12-1-55
Con Tues	_

Pool Beein	Dekota		Formation_	1)ekota		_County		Sen June	<u> </u>
			Special							
ompany PAN ANDR										
nitSe										
asing 4-1/2 Wt										
ubing 2-3/8 Wt										
as Pay: From_										
roducing Thru:	Casin	g	Tubi	.ng	Sine	Type We	ll nhe ad- G.	G. or (.O. Dual	·
ate of Completi	.on:	5-30-64	Packer	14	NEWS DITTE	Reservo	ir Temp.			
					ED DATA					
l . L . 3 Misses als	Anustracia	↑ (Choko)				Type Ta	os T	lange	
ested Through							·			
(#3800#-)	Flo (Choke	w Data) Pres	s. Diff.	Temp.	Tubing Press.	Temp.	Press.	Temp.	Dur	ation
lo. (Line)	(GITTE					o _F ,	i	ł	i of	Flow
Size I 9 deys	Size	psi	g h _w	F •	1666		1605			
. Z lach	,750	_ W			204		636		3 1	<u>. </u>
•										
)• !				 -	<u> </u>	<u>. </u>			<u> </u>	
Coossini			Pressure F		CULATION Temps		Compr	ess.	Rate of	Flow
Coefficie		<i></i>		rac	cor	raccor	Fact	or	Q-MCFPI @ 15.025)
(24-Hou	r) 7	h _w p _f	psia		t	Fg	Fpv	025	253	
12.3650			216	1.90		.9252				
•										
s Liquid Hydro avity of Liqui	d Hydrod	carbons		SSURE (cf/bbldeg.	CALCUIATI • •	Speci	ific Grav	rity Flo	arator G wing Flu 2,636	id
P _w	2			T .	- 2)2	n ^	P _c -P _v	2 .	al.	D D
No. Pt (psia)	$P_{\mathbf{t}}^{2}$	F _c Q	$(F_cQ)^2$		$F_cQ)^2$ $1-e^{-s}$	P_w^2	rc-rv		P _W	Pw Pc
1 (pola)				 		399,434	2,224,9	76	- 	
2 · · · · · · · · · · · · · · · · · · ·										
				4			 			
		286		MCFPD	; n	.75				
5.	ial.			-	,			W. C.	The state of the s	
Absolute Potent	AMERICA	AL PATRO						ATT	115	
Absolute Potent COMPANY ADDRESS ACENT and TITLE	Augustes D. Ben	A PATRICI	sington, Bo	v Herie				OFF	VD	
Absolute Potent	Augustes D. Ben	A PATRICI	sington, Bo	v Herie				ALL	21964	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{w}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{w}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.