Address 207 Petr. Club Plaza


Fermington, New Mexico

京出た~707

Budget Bureau No. 42-R358, Approval expires 12-31-60.

Ų.					
•	1-F				

Land	Office				
Loase	No.	Mi-	0352	3	
Jnit .					



Form 9-331 a (Feb. 1951)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(SUBMIT IN TRIPLICATE)

He	11	oway	Fed.	"B"
				_

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHOT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALIER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
	Grade Vinder (Control of the Control
(INDICATE ABOVE BY CHEC	CK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	Habasanaa 28 1042
	February 26 , 1962
Well No a is located was fit	from $\begin{bmatrix} N \\ R \end{bmatrix}$ line and -990 ft. from $\begin{bmatrix} E \\ R \end{bmatrix}$ line of sec. -6
wen ivo is located typ. it	inte and
ME Sec. 6 26 N (Twp.)	11 W
	(Range) (Meridian)
Basin Bakota S	n han Herico County or Subdivision) (State or Territory)
The elevation of the derrick floor above	sea level is 6136 ft. G.L.
D	DETAILS OF WORK
(State names of and expected depths to objective sands:	DETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- and all other important proposed work)
(State names of and expected depths to objective sands; a ing points, a 2/26/62 Man Drlg. Co. moved on surface hole, drld. 23/8tar csg @ 195° cements	show sizes, weights, and lengths of proposed casings; indicate mudding jake company
(State names of and expected depths to objective sands; a ing points, a 2/26/62 Man Drlg. Co. moved on surface hole, drld. 23 Star csg @ 195' cements WCC 19 hrs. pressure to	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work) location rigged up & spudded • 6:30 p.m. in 13 3/4" 0', ran & set 8 jts. 206' of 10 3/4" 32.75# Lone ed w/150 ex HA-5 2% gel, plug dewn • 3:00 a.m. 27th est w/700# for 30 minutes, held 0K. Drilling
(State names of and expected depths to objective sands; a ing points, a 2/26/62 Man Drlg. Co. moved on surface hole, drld. 23/8tar csg @ 195° cements	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work) location rigged up & spudded • 6:30 p.m. in 13 3/4" O', ran & set 8 jts. 206' of 10 3/4" 32.75# Lone ed w/150 ex HA-5 2% gel, plug dewn • 3:00 a.m. 27th est w/700# for 30 minutes, held OK. Drilling roval in writing by the Geological Survey before operations army be commenced.

Original signed by Carl W. Smith

Title Superintendent