

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau/No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. UNIT AGREEMENT NAME Bierfano Unit	
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME Bierfano Unit	
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico - 87401		9. WELL NO. 304	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Sec. 11, T. 26-N, R. 10-W		10. FIELD AND POOL, OR WILDCAT Basin Dakota	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6645' OL	
		12. COUNTY OR PARISH San Juan	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 2-11-69 spudded well, drilling surface hole.

On 2-13-69 ran 7 joints - 5 1/2", 24", J-75 casing (221') set at 662' w/150 sacks of cement circulated to surface. W.C.C. 12 hours, tested w/600 / 30 Min. C. K.

On 3-1-69 T.B. 6635'. On 215 joints 4 1/2", 10.5", J-75 casing (664') set at 6635'. Float collar set at 6642', second stage tool at 4,592', third stage tool at 2,390'. Cemented first stage w/270 sacks cement, second stage w/200 sacks cement, third stage w/170 sacks of cement. W.C.C. 10 hours.

On 3-2-69 F.B.T.T. 6642', tested casing to 4000. C. K. Spotted 250 gal. 7 1/2" HCL. Perf. 6774-66', 6766-6642', 6635-47' w/10" L. Frac w/40,000 20/40 sand, 30,000 gal. water. Max. pr. 4000, H.P. 1000, avg. tr. pr. 3075, I.R. 36 H.P. Logged 2 sets of 10 balls, flushed w/4000 gal. water. I.R. 1000, 5 Min. 600.

18. I hereby certify that the foregoing is true and correct

SIGNED Carl E. Matthews

TITLE Petroleum Engineer


DATE 3-4-69

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____



RECEIVED

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement; otherwise, depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of placing of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection and approval of the abandonment.