

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR
BOX 289, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 910'S, 1110'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Rincon Unit

8. FARM OR LEASE NAME
Rincon Unit

9. WELL NO.
97A

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-27-N, R-6-W
NMPM

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6606' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/10/78: T.D. 3527'. Ran 112 joints 7", 20#, K-55 intermediate casing, 3516' set 3527'. Cemented with 248 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2200'.

10/13/78: TD 5853'. Ran 72 joints 4 1/2", 10.5#, K-55 casing liner, 2610' set 3243-5853'. Float collar set at 5835'. Cemented with 431 cu. ft. cement. WOC 18 hours.

11/7/78: PBT.D. 5835'. Tested casing to 3500#, OK. Perfed 4789, 4794, 4868, 4891, 4896, 4919, 4926, 4933, 4959, 4966, 4973, 4980, 5010, 5240, 5384 with 1 SPZ. Fraced w/47,500# 20/40 sand and 95,000 gal. water. Flushed w/6951 gal. water. Perfed 5430, 5437, 5444, 5454, 5460, 5466, 5472, 5478, 5484, 5490, 5509, 5542, 5549, 5564, 5574, 5586, 5610, 5634, 5683, 5709, 5721, 5752, 5759, 5778, 5786, 5822 w/1 SPZ. Fraced

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Duacs TITLE Drilling Clerk DATE 1/15/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

JAN 18 1979

U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

86,500# 20/40 sand and 173,000 gal. water. Flushed
w/7245 gal. water.