

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Mobil Oil Corporation
3. ADDRESS OF OPERATOR
9 Greenway Plaza, Suite 2700, Houston, TX 77046
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 880' FEL & 184' FSL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

NOV 6 1978

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed Procedure:

1. Pull rods, pump and tubing.
 2. Set cement retainer at approx. 6300', 100' above the Penn Perforation 6408'-6460'. Squeeze Penn Perforations w/30 sxs.
 3. Run free point on 5½" production casing, cut and pull casing at indicated free point. (Cmt top at 5500' from temperature survey).
 4. Circulate hole with mud-laden fluid (minimum weight 95#/gal brine).
 5. Spot 50x 200' cement plug across 5½" casing stub with 150' above and 50' below cut-off point.
 6. Spot 60x 200' plug from 4250' to 4450' (base of De Chelly).
 7. Spot 60x 200' plug from 3650' to 3850' (top of De Chelly).
 8. Spot 45x 150' plug across the 8-5/8" casing shoe with 50' inside the casing and 100' outside.
- (Over)

Subsurface Safety Valve: Manu. and Type _____ Ser @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Virginia Shover TITLE Authorized Agent DATE October 31, 1978

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
NOV - 8 1978
U. S. GEOLOGICAL SURVEY
WASHINGTON, D. C.

9. Spot 15x 50' cement surface plug. Erect marker.
10. Clean up and seed location.

NOTE: This procedure has been discussed with Mr. P. T. McGrath, USGS, Farmington.

STATEMENT OF SURFACE RESTORATION INTENTION
ATTACHMENT TO USGS FORM 9-331, SUNDRY NOTICE OF INTENT TO ABANDON

Applicable To: Mobil Oil Corporation
Three Greenway Plaza East, Suite 800
Houston, Texas 77046

Lease Name: Navajo

Well No: 5

Location: 800' FEL & 184' FSL of Sec. 9, T-26-N, R-18-W,
San Juan Co., NM.

This is to advise your office that surface restoration associated with the above described proposed plugging and abandonment will be conducted in accordance with applicable rules and regulations of the United States Geological Survey and the New Mexico Oil Conservation Commission; and in accordance with any existent agreement with the surface landowner, or in a manner arrived at by agreement with the surface landowner.

Such restoration work will include:

Backfilling of all pits and cellar. Levelling or contouring
the location site. Clearing the location area of junk.

FORM 9-331 Dated: 10/31/78

RECEIVED
NOV 6 1978

U. S. GEOLOGICAL SURVEY