iso congress) 2-conthland Fogally. 130 130 (Van Ryan) Form approved. Form 9-331 (May 1963) UNITED STATES SUBMIT IN TRIPLICATES
DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side) Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM 0558240 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE. NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 3 2 5 5 7. UNIT AGREEMENT NAME the to GAS WELL WELL | OTHER 8. FARM OR LEASE NAME. NAME OF OPERATOR County Seat Dugan Production Corp. 9. WELL NO. 1. 2 3 3. ADDRESS OF OPERATOR Box 234, Farmington, NM 87401 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 10. PIELD AND POOL, OR WILDCAT NIPP - PC J1. SEC., T., R., M., OR BLK. AND SHURVET OR ARMA 790' FSL - 870' FWL Sec 21 126N R12W 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) San Juan 6038' GR 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data: BURSEQUENT REPORTION: 5 NOTICE OF INTENTION TO: DEFAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT-OFF ALTERINO CASINO PRACTURE TREATMENT FRACTURE TREAT MULTIPLE COMPLETE SHOOTING OR ACIDIZING TABANDONMENT SHOOT OR ACIDIZE ABANDON 4 spud, surface csg, _czg. CHANGE PLANS (Other) REPAIR WELL (NOTE: Report results of multiple completion on Well-Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Spudded 6-1/4" hole at 10:30 a.m. Moved in Morrow Drlg. Company. Drilled to 44.50'. Ran one joint 5-1/2" 14# used csg set @ 44.60' 7-13-78 Cemented w/8 sx. TE 43.60'. Job complete 12:15 p.m. 7-16-78 TD 1235'. Finished drlg 4-3/4" hole @ 9:00 a.m. Cixculated and conditioned hole. Laid down drill pipe. Ran Welex IES to TD. Ran 40 jts 2-7/8" OD 6.5 $\frac{4}{10}$ J-55 8R EUE thg for esg. TE 1217.23' set @ 1217' GR. Hydro tested the to 4000 psi - OK. Preflushed hole w/100 gal mud sweep. Reciprocated pipe and had good mud returns while cementing. Lost circulation after dropping plug. Cemented w/75 sx 2% Lodense w/1/4# cello flake per sx. Bumped plug w/2500 psi. Released to 750 psi. Shut In. POB 7:10 p.m. 7-15-78. off of JUL 2 1 1978 22 18. I hereby certify that the foregoing is true and correct DIST noc SIGNED TITLE DATE (This space for Federal of State office use) Ben. **PARTICLE SESSION**

TITLE

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

PATRILLE M.