

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
DOME PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR 501 Airport Drive  
Suite 107, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1120' FSL, 790' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) SPUD & SET SURFACE	<input type="checkbox"/>		<input type="checkbox"/>

NOO-C-14-20-7476

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
NAVAJO

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
DOME NAVAJO 13-26-13

9. WELL NO.  
4

10. FIELD OR WILDCAT NAME  
WAW FRUITLAND PICTURED CLIFF

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
SEC. 13, T26N, R13W

12. COUNTY OR PARISH  
SAN JUAN

13. STATE  
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6068 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 8 3/4" hole at 9:45 AM, 11/07/79. Drilled to 100' Ran 3 jts. 95',  
5 1/2", 15.5# K-55 LT&C casing. Casing landed at 97' GL. Cemented w/ 35 sacks  
class "B" cement w/ 2% CaCl. Plug down at 1:30 PM, 11/07/79. Circulated  
cement.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLLINGSWORTH TITLE DRG. & PROD. FOREMAN DATE November 9, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

\*See Instructions on Reverse Side