

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1650'N, 800'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-14-80: Spudded well. Drilled surface hole. Ran 3 joints 8 5/8", 24#, J-55 surface casing 123' set at 135'. Cemented w/ 106 cu. ft. cement. Circulated to surface. WOC 12 hours; held 600#/30 minutes.

12-18-80: TD 2207'. Ran 82 joints 2 7/8", 6.4#, J-55 production casing 2196' set at 2207'. Baffle set at 2197'. Cemented w/ 354 cu. ft. cement. WOC 18 hours. Top of cement at 1100'.

12-23-80: PBTD 2197'. Tested casing to 4000#, OK. Perfed: 1957, 1968, 1975, 1983, 1988, 1994, 2005, 2011, 2017, 2028' W/1 SPZ. Fraced w/ 67,000# 10/20 sand, 72,000 gal. wtr. Flushed w/ 500 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. D. Busco TITLE Drilling Clerk DATE January 13, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY

ACCEPTED FOR RECORD

NMOCC

JAN 21 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT