

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
John H. Hill and Gordon L. Llewellyn
3. ADDRESS OF OPERATOR Suite 140 Campbell Centre
8350 North Central Expressway Dallas, Tx 75206
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1085' FNL, 840' FWL Sec. 9
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

JAN 11 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF-078384
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Newsom B
9. WELL NO.
16
10. FIELD OR WILDCAT NAME
Ballard Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/4 Sec. 9 T-26N R-8W NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6382' GL, 6392' KB

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11" hole @ 1:30 AM 1-3-80, drilled to 180', ran 4 jts 7 5/8" used 29.7# N-80 LT&C casing, set @ 180' KB. Cemented w/140 sks Class B, 1/4# flocele/sk and 3% CaCl. Plug down @ 9 AM 1-3-80, cement circulated. WOC 12 hrs, tested casing and BOP to 1000# for 15 min, held OK.

Drilled 6 3/4" hole to 2440', ran IES log, ran new 2 7/8" EUE 6.5# J-55 casing, set @ 2425', cemented w/125 sks 65-35 posmix, 12% gel, 6 1/4# gilsonite/sk and 125 sks 50-50 posmix, 6 1/4# gilsonite and 6# salt/sk. Plug down @ 4 PM 1-6-80. Approximate top of cement 920'. WOC.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED W. Llewellyn TITLE Superintendent DATE 1-9-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOC

ACCEPTED FOR RECORD

JAN 17 '80

FARMINGTON DISTRICT

BY _____