

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Supron Energy Corp. c/o John H. Hill, et al.
3. ADDRESS OF OPERATOR Kysar Building, Suite 020
300 W. Arrington, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1080' FNL & 1610' FEL (NW NE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF - 078432
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Hodges
9. WELL NO.
#19
10. FIELD OR WILDCAT NAME
Ballard Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28 T26N R8W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6475' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 6¼" hole to Total Depth 2600', at 10:45 P.M., 11/27/80.
2. Logged well, ran Gamma Ray and Neutron logs.
3. Ran 86 joints (2567') of new 2 7/8", 6.4#, 10RD. NUE casing.
4. Cemented with 400 sacks 50/50 Poz, 6% Gel, ½ Cu. Ft. Perlite per sack. Tailed in with 150 sacks Class B cement. Bumped plug to 2500'. Circulated 30 barrels cement.
5. Test water shut-off to 800# with 10", 900 Series Gardner-Denver Blow-out Preventer. Job complete at 3:45 P.M., 11/29/80.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Norman V. Wallis TITLE Exploration and Development Superintendent DATE DEC 3 1980

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

FARMINGTON DISTRICT
BW

NMOCC

