

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building  
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 870' FSL & 1030' FEL (SE SE)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

SF - 078430

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
Newsom "A"

9. WELL NO.  
12

10. FIELD OR WILDCAT NAME  
Ballard Pictured Cliffs


11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3 T26N R8W

12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6838' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded a 12 $\frac{1}{4}$ " hole at 6:00 P.M., 4/29/81. Drilled to 250'. Circulated cement.
2. Ran 7 joints (212.36') of new 8 5/8", 24#, LS, R-2 ST&C casing.
3. Pipe set and cemented at 224.36' RKB.
4. Cemented with 200 sx. Class "B" cement 2% Calcium Chloride and  $\frac{1}{4}$ # Flo-cele per sack.
5. Plug down at 2:30 A.M., 4/21/81.
6. Circulation good throughout job. Circulated 20 barrels cement.
7. Check water shut-off to 600#, with 8" 4000 Series Shaffer Blow-out Preventer.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas V. Wallis TITLE Exploration/Development Superintendent DATE April 22, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE ACCEPTED FOR RECORD  
CONDITIONS OF APPROVAL, IF ANY:

INMOCC

\*See Instructions on Reverse Side

APR 24 1981

FARMINGTON DISTRICT