

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 860' FSL & 910' FEL (SE SE)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF - 078433

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Newsom

9. WELL NO.

17-E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20 T26N R8W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. AP. NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6368' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 12 1/4" surface hole at 9:00 P.M., 2/3/81. Drilled to 324'. Circulated cement.
2. Ran 3 joints (131.6') of new 8 5/8", 17#, X-42, R-3 ST&C casing and 4 joints (164.2') of new 8 5/8", 23#, K-55, R-3 ST&C casing.
3. Set and cement at 295.80'.
4. Cemented with 275 sx. Class "B" cement, 3% Calcium Chloride and 1/4# Flo-cele per sack.
5. Plug down at 5:45 A.M., 2/4/81.
6. Circulation good throughout job. Circulated 15 sx. good cement.
7. Check water shut-off at 600# with 10", 3000 Series Shaffer Blow Out Preventer.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ferman V. Wallin TITLE Exploration/Development Superintendent DATE February 6, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC